

Portland State University

**PDXScholar**

---

PSU Transportation Seminars

Transportation Research and Education Center  
(TREC)

---

11-22-2013

# Piloting Portland's MultiModal Arterial Performance System

Shaun Quayle

*Kittleson & Associates, Inc.*

Follow this and additional works at: [https://pdxscholar.library.pdx.edu/trec\\_seminar](https://pdxscholar.library.pdx.edu/trec_seminar)



Part of the [Transportation Commons](#), and the [Urban Studies and Planning Commons](#)

**Let us know how access to this document benefits you.**

---

## Recommended Citation

Quayle, Shaun, "Piloting Portland's MultiModal Arterial Performance System" (2013). *PSU Transportation Seminars*. 89.

[https://pdxscholar.library.pdx.edu/trec\\_seminar/89](https://pdxscholar.library.pdx.edu/trec_seminar/89)

This Book is brought to you for free and open access. It has been accepted for inclusion in PSU Transportation Seminars by an authorized administrator of PDXScholar. Please contact us if we can make this document more accessible: [pdxscholar@pdx.edu](mailto:pdxscholar@pdx.edu).

# Piloting Portland's Multi-Modal Arterial Performance System

November 22, 2013



## Why Performance Measures?

- > "What Gets Measured Gets Done"
- > Reality-Focus rather than Prediction
- > MAP-21 → Accountability



[Hoococonnect.blogspot.com](http://Hoococonnect.blogspot.com)



## Why Not Performance Measures?

- It costs too much
- What to collect & where to start?
- Lacking reliability, confidence, or resolution in data
- Data overload...how to make it useful?
- Software gives me answers that are “close enough”




 KITTELSON & ASSOCIATES, INC.  
TRANSPORTATION ENGINEERING/PLANNING



## Arterial Performance Background

- NCHRP 3-79: Measuring the Performance of Auto Traffic on Urban Streets

- Delay & Queue Measurement
- Running Time



Purdue Univ. – NCHRP 3-79



## Concept for Arterial Performance Management

- Agree upon **outcomes and measures**
- Establish **best** data collection **technologies & approach**
- **Leverage existing** infrastructure and mainstream collection
- **Fuse** different **data sources** into a complete picture
- Establish **institutional agreements and resources**



## Operations Arterial Performance Objectives

- Reduce congestion
- Minimize delay
- Minimize travel time
- Minimize queue spillback
- Reduce travel speeds
- Reduce traveler frustration
- Better inform traveler(s)

*Monitor to determine/confirm problem, appropriate solutions, and on-going performance metrics*



## Users of Arterial Performance Data & Information

### Planners

- want to understand future needs and how to invest wisely

### Engineers/Operators

- want to know how well this system is working

### Modelers & Researchers

- want to investigate trends and ideas

### Traveling Public

- want information about their trip



## Portland Multimodal Arterial Performance Management implementation guidance document



February 2013



Prepared for





METRO

Prepared by



In cooperation with






## Criteria for Top Arterial Performance Candidates

- Street is of Regional Importance
- Frequent Transit Service
- Basic Corridor Readiness
- Signal & Comm System to Automate




## Pilot Project – 82<sup>nd</sup> Avenue Key Findings

- Successfully Leveraged Existing Infrastructure to Semi-Automate Multi-modal Data Sources
- Data interfaces are missing or incomplete
- Recognize strength & weakness of data sources
  - Ease of use, biases, etc...
- Location, Location, Location







# System Detection



Rob Klug, Clark Co

**K** KITTELSON & ASSOCIATES, INC.  
TRANSPORTATION ENGINEERING/PLANNING

# Length-Based Classification



# Intersection Count Data

View Volume Logs For 10 - US26 @ 185th 24 - 185th @ Cornell

[Print Volumes](#) [Display Graph](#)

Enter Date: 10/25/2011  
 Enter Start Time: 16:00 Enter End Time: 17:00

NORTHWEST SIGNAL

Volume Logs For - 10 - US26 @ 185th 24 - 185th @ Cornell

Tuesday, September 24, 2013 12:27

Number of Records: 4 Sample Period (min): 15  
 Date: Tuesday, October 25, 2011 Search Time: 16:00 - 17:00

Detector	1	2	3	4	5	6	7	8
Volume	114	122	132	206	190	205	190	270
Detector	9	10	11	12	13	14	15	16
Volume	407	989	747	0	0	385	537	656
Detector	17	18	19	20	21	22	23	24
Volume	0	198	522	954	4	274	235	315
Detector	25	26	27	28	29	30	31	32
Volume	80	455	533	1	0	0	0	0




- Dates of Stored Volume Logs
- 10/27/11
  - 10/26/11
  - 10/25/11
  - 10/24/11
  - 10/23/11
  - 10/22/11
  - 10/21/11
  - 10/20/11
  - 06/01/11
  - 05/31/11
  - 05/30/11
  - 05/29/11
  - 05/28/11
  - 05/27/11

# Truck Priority



**K** KITTELSON & ASSOCIATES, INC.  
 TRANSPORTATION ENGINEERING/PLANNING

## Bicycle Count Stations



### A BIKE DETECTION (NEW)


Installed parallelogram inductive bike loop to count bike traffic.

#### Performance Metrics

Name	NB/SB
Weekday PM Peak Hour Bike Volume	13 / 7
Weekday Bike ADT	160 / 100
Weekend Bike ADT	130 / 85



## Transit Performance Data (TriMet)



### F TRIMET CAD/AVL DATA


TriMet AVL data provides real time vehicle tracking and can be aggregated to determine on-time performance for bus routes.

#### Bus On-time Performance

##### PM Peak hour

NB Route 72	84%
SB Route 72	78%

Data from TriMet; Fall 2012 (3:30 - 5:30 PM)



### G TRANSIT SIGNAL PRIORITY (TSP)

Transit signal priority (TSP) operates by transmitting location and vehicle information to traffic signals which prioritize transit vehicles at signals


#### Transit Signal Priority Performance 82nd/Woodward

Direction	NB	EB	SB	WB
Calls Per Hour	0	-	8.8	-
Avg. Extension (sec)	0	-	11	-




Data collected from TransSuite; Oct 15 - 19, 2012

# Bluetooth™ “Probe” Permanent Locations



	3/4/12 – 3/10/12	9/9/12 – 9/15/12	Delta
82 <sup>nd</sup> : Glisan - Springwater	454	497	+ 9.5%
82 <sup>nd</sup> : Springwater - Glisan	421	451	+ 7.1%
Powell: 8 <sup>th</sup> - 42 <sup>nd</sup>	3064	3159	+ 3.1%
Powell: 42 <sup>nd</sup> – 8 <sup>th</sup>	3566	3689	+ 3.5%

# Bluetooth™ “Probe” Speed & TT



## Probe Data → 24/7

Pre-SCATS Plan	Periods	Buffer IndexBefore <sup>1</sup>	Eastbound	Δ in Buffer Index
			Buffer IndexAfter <sup>1</sup>	
<b>Weekdays</b>				
Free	12:00 AM – 6:30 AM	46%	42%	-4%
Coord	6:30 AM - 9:00 AM	39%	43%	4%
Coord	9:00 AM - 3:00 PM	41%	44%	3%
Coord	3:00 PM - 6:30 PM	70%	55%	-15%
Coord	6:30 PM - 8:30 PM	36%	37%	1%
Free	8:30 PM – 11:59 PM	35%	31%	-4%
24 Hour Average		63%	54%	-9%
<b>Saturdays</b>				
Free	12:00 AM - 9:00 AM	34%	38%	4%
Coord	9:00 AM - 7:30 PM	32%	35%	3%
Free	7:30 PM - 11:59 PM	32%	32%	0%
24 Hour Average		37%	39%	2%




## Bluetooth™ Origin-Destination

Butler Street as Origin



Loc	Destination	Number of Trips	Percentage
48th Ave		2628	61.6%
Destination		4282	38.4%

# Fleet "Probe" Data (Inrix™)



# Probe Data Comparison – Pilot Evaluation

## D BLUETOOTH MAC ADDRESS READER

A Bluetooth MAC address reader is used to measure segment travel time, speed and origin-destination data.



### Performance Metrics

Travel Time From Foster Road (NB)

→ 10:40 mins

Travel Time To Foster Road (SB)

← 10:41 mins

Data collected Portal; from Feb 10 - Oct 12, 2012 (4 - 6 PM)

## E INRIX DATA SEGMENT

Inrix data is used to measure travel time and average speed data for a segment. (Inrix segment highlighted below)


### Performance Metrics

Travel Time SE Foster to NE Glisan (NB)

→ 8:10 mins


Travel Time NE Foster to SE Stark (SB)

← 7:58 mins




Data based on Inrix 2010 average weekday (4 - 6 pm)

# Controller Logs = Timing Effectiveness



**K** KITTELSON & ASSOCIATES, INC.  
TRANSPORTATION ENGINEERING/PLANNING

# Service Delay Log



**K** KITTELSON & ASSOCIATES, INC.  
TRANSPORTATION ENGINEERING/PLANNING



# Service Delay Log: Pedestrians

## B PEDESTRIAN DETECTION


With pedestrian detection, delay and call request information can be collected and logged by a 2070 traffic controller

## AM/PM Peak Period Pedestrian Performance

Cross Walk Phase	2	4	6	8
Button Calls Per Hour	-	16 / 58	-	16 / 58
Delay to Serve Call (sec)	-	30 / 35	-	30 / 35




# % Arrival on Green = Timing Effectiveness




WESTBOUND

Source: NWS Voyage Manual





## Red Clearance Extension



## Summary Arterial Performance Measures

- > Transit
  - On-Time Performance, Ons/Offs, Travel Time, # of TSP requests
- > Pedestrian
  - Number of ped phases served, Transit Ons/Offs, ped delay
- > Bicycle
  - Number of bikes, bicycle delay (if own detector input)



Photo: Greg Raisman

## Summary Arterial Performance Measures

### > Freight

- # of trucks (length-based), # of truck priority requests

### > Autos

- # of vehicles (sys det or controller log), travel time, speeds, delay, % arrival on green, max outs v. gap outs



**K** KITTELSON & ASSOCIATES, INC.  
TRANSPORTATION ENGINEERING/PLANNING

## Next Steps – Enhanced Logging

- > Delay by Input
- > TSP
- > Red Extension




				Intersection Level of	Phase Level of Service												
					1	2	3	4	5	6	7	8					
"4- TP Max'd Out, NO Conflict"																	
"5- Priority Override"																	
"6- Override Timeout Fault"																	
"7- TP Input Failed"		Time	Type	Detect.	Delay Time	Mode	Max Plan	Service Plan	Level of								
"8- Inhibit (Various)"	60	14:45:00	LDS						25 (C)	86	3	57	54	35	15	37	62
"9- TP Input Returned to Normal"	61	15:00:00	LDS						28 (C)	93	3	70	100	26	11	47	74
"10- Min Re-service Refusal"	62	15:15:00	LDS						20 (B)	61	1	39	70	28	10	53	58
"11- Inhibit Transit Priority Applied"	63	15:30:00	LDS						28 (C)	86	4	59	88	31	11	47	54
	64	15:45:00	LDS						26 (C)	57	2	34	91	32	11	51	61
	65	16:00:00	LDS						25 (C)	104	4	54	70	37	8	41	49
"12- Force Off Termination"	66	16:15:00	LDS						28 (C)	68	2	52	94	47	14	54	60
"13- TP Input Went Inactive In TP Green"																	
"14- TP Clear Input Active In TP Green"																	
"15- TP Went Away During Bus Extend"																	
"16- Truck Caused TP"																	
"17- Truck Arrived Late, no TP"																	
"18- TP Remains Active After Extension"																	
"19- Preempt Override"																	
"20- TP Max'd Out, With Conflict"																	

**K**

## Next Steps – Improved Interfaces



Max Plan	Service Plan	Intersection Level of	Phase Level of Service											
			1	2	3	4	5	6	7	8	9			
	25 (C)	86	3	57	54	35	15	37	62					
	28 (C)	93	3	70	100	26	11	47	74					
	20 (B)	61	1	39	70	28	10	53	58					
	28 (C)	86	4	59	88	31	11	47	54					
	26 (C)	57	2	34	91	32	11	51	61					
	25 (C)	104	4	54	70	37	8	41	49					
	28 (C)	59	2	52	84	47	14	54	60					



Date/Time	Count	Gap	Date/Time	Count	Gap
12/01/2012 09:00:00	4	0	12/02/2012 05:05:00	2	0
12/01/2012 10:00:00	15	0	12/02/2012 06:05:00	1	0
12/01/2012 11:00:00	19	0	12/02/2012 07:05:00	2	0
12/01/2012 12:00:00	29	0	12/02/2012 08:05:00	4	0
12/01/2012 13:00:00	36	0	12/02/2012 09:05:00	9	0
12/01/2012 14:00:00	31	0	12/02/2012 10:05:00	10	0
12/01/2012 15:00:00	14	0	12/02/2012 11:05:00	14	0
12/01/2012 16:00:00	16	0	12/02/2012 12:05:00	29	0


## Next Steps – Validation & Research

➤ Inrix, Bluetooth, Bike Counts, Controller Logs, GUIs



## Next Steps – Continued Pilot Projects

- Outreach Workshops
- Target Funded Upcoming Capital Projects
- Incorporate into Design Specs/Guidance



## Successful Arterial Performance

- **Quality Data**
  - Validate!
- **Appropriateness** for Objectives/Outcomes &
  - Know outcomes first
  - No gadgets for gadgets sake
- **Ease of Use** are of the utmost importance
  - Time is a valuable commodity
  - Interfaces to other systems/devices

## Questions / Discussion?

> Shaun Quayle

[squayle@kittelson.com](mailto:squayle@kittelson.com); 503-228-5230

