Portland State University

PDXScholar

Mathematics and Statistics Faculty
Publications and Presentations

Fariborz Maseeh Department of Mathematics
and Statistics

8-3-2017

A Finite Difference Method for Off-fault Plasticity throughout the Earthquake Cycle

Brittany A. Erickson

Portland State University, berickson@pdx.edu

Eric M. Dunham

Stanford University

Arash Khosravifar

Portland State University, karash@pdx.edu

Follow this and additional works at: https://pdxscholar.library.pdx.edu/mth_fac

Part of the [Mathematics Commons](#), [Physics Commons](#), and the [Tectonics and Structure Commons](#)

Let us know how access to this document benefits you.

Citation Details

Brittany A. Erickson, Eric M. Dunham, Arash Khosravifar, A Finite Difference Method for Off-fault Plasticity throughout the Earthquake Cycle, *Journal of the Mechanics and Physics of Solids* (2017), doi: 10.1016/j.jmps.2017.08.002

This Post-Print is brought to you for free and open access. It has been accepted for inclusion in Mathematics and Statistics Faculty Publications and Presentations by an authorized administrator of PDXScholar. Please contact us if we can make this document more accessible: pdxscholar@pdx.edu.

A Finite Difference Method for Off-fault Plasticity throughout the Earthquake Cycle

Brittany A. Erickson^a, Eric M. Dunham^{b,c}, Arash Khosravifar^d

^a*Department of Mathematics and Statistics, Portland State University, Portland, OR 97201, USA. berickson@pdx.edu*

^b*Department of Geophysics, Stanford University, Stanford, CA, USA.*

^c*Institute for Computational & Mathematical Engineering, Stanford University, Stanford, CA, USA.*

^d*Department of Civil and Environmental Engineering, Portland State University, Portland, OR, USA.*

Abstract

We have developed an efficient computational framework for simulating multiple earthquake cycles with off-fault plasticity. The method is developed for the classical antiplane problem of a vertical strike-slip fault governed by rate-and-state friction, with inertial effects captured through the radiation-damping approximation. Both rate-independent plasticity and viscoplasticity are considered, where stresses are constrained by a Drucker-Prager yield condition. The off-fault volume is discretized using finite differences and tectonic loading is imposed by displacing the remote side boundaries at a constant rate. Time-stepping combines an adaptive Runge-Kutta method with an incremental solution process which makes use of an elastoplastic tangent stiffness tensor and the return-mapping algorithm. Solutions are verified by convergence tests and comparison to a finite element solution. We quantify how viscosity, isotropic hardening, and cohesion affect the magnitude and off-fault extent of plastic strain that develops over many ruptures. If hardening is included, plastic strain saturates after the first event and the response during subsequent ruptures is effectively elastic. For viscoplasticity without hardening, however, successive ruptures continue to generate additional plastic strain. In all cases, coseismic slip in the shallow sub-surface is diminished compared to slip accumulated at depth during interseismic loading. The evolution of this slip deficit with each subsequent event, however, is dictated by the plasticity model. Integration of the off-fault plastic strain from the viscoplastic model reveals that a significant amount of tectonic off-

Preprint submitted to J. Mech. Phys. Solids

August 16, 2017

set is accommodated by inelastic deformation (~ 0.1 m per rupture, or $\sim 10\%$ of the tectonic deformation budget).

Keywords: earthquake cycle, plasticity, Drucker-Prager, finite difference method

1. Introduction

Field observations reveal regions of highly damaged rock (containing abundant microfractures) surrounding a fault core, which many attribute to thousands of years of seismogenic cycling during which earthquakes shatter the rocks in the vicinity of the fault (*Chester and Logan, 1986; Chester et al., 1993; Shipton et al., 2005; Mitchell and Faulkner, 2009; Faulkner et al., 2010; Ben-Zion and Sammis, 2011*). Understanding how an earthquake will propagate is intimately tied to the evolution of these damage zones. Important and unsolved problems include the relationship between the degree of off-fault yielding and mechanical properties of fault zone material, how damage zones evolve with increasing cumulative slip, and how damage zones affect subsequent rupture.

Current models for dynamic rupture have led to much insight into earthquake propagation, the generation of high-frequency ground motion, and the influence of plasticity on rupture propagation (*Templeton and Rice, 2008; Ma and Andrews, 2010; Dunham et al., 2011a,b; Kaneko and Fialko, 2011; Xu et al., 2012a,b; Shi and Day, 2013; Gabriel et al., 2012, 2013*). Although the inclusion of a plastic material response has been shown to reduce stress and slip velocities at the rupture front to reasonable values, little work has been done to understand the evolution of a damage zone (and its impact on rupture) over multiple event sequences. In particular, most dynamic rupture models currently make the assumption of a uniform background stress and are limited to single-event simulations where rupture is artificially initiated via a stress perturbation imposed on the fault. Earthquake cycle models, on the other hand, generate self-consistent initial conditions because of their ability to handle varying time scales. Cycle models developed in the boundary integral or boundary element context were limited to simulations in a uniform, linear elastic whole- or half-space (*Lapusta et al., 2000; Tullis et al., 2012*). Recent developments, however, have shown how to incorporate more realistic features (material heterogeneities or inelastic deformation, for example) into the earthquake cycle framework (*Johnson and Segall, 2004; Kaneko*

et al., 2011; Barbot et al., 2012; Aagaard et al., 2013; Erickson and Dunham, 2014; Thompson and Meade, 2016; Allison and Dunham, 2017).

In this work we study the role of plasticity throughout the earthquake cycle. The computational method is developed for the classical antiplane problem of a vertical strike-slip fault governed by rate-and-state friction. The off-fault material is idealized as a Drucker-Prager elastic-plastic solid and stresses are constrained by a depth-dependent yield condition. Inertia is approximated with radiation damping. Within the context of a time-stepping method, we solve the resulting equilibrium equation (a nonlinear, elliptic partial differential equation) for the displacement increment.

Although computational plasticity is most commonly addressed in a finite element framework, we develop a finite difference method, as the latter is easy to program, efficient, and can be applied in a straightforward manner in order to obtain a numerical approximation to the solution (Scalerandi et al., 1999). Recent work in summation-by-parts finite difference methods has furnished high-order accurate schemes that enforce boundary and interface conditions in a stable manner (through the simultaneous-approximation-term technique) (Kreiss and Scherer, 1974, 1977; Nordström et al., 2007; Svärd and Nordström, 2014). These methods provide a framework for proving convergence for linear and nonlinear problems, which is fundamental in order to obtain credible numerical approximations. In this work, an initial analysis is done of the underlying continuum problem to show it satisfies an energy estimate (in this case, dissipation of mechanical energy in the absence of non-trivial boundary conditions or source terms). The computational method then provides a spatial discretization that mimics the energy estimate of the continuum problem and proves stability of the method.

The paper is organized as follows: In section 2 we state the continuum problem solved in this work. A rate-and-state frictional fault is embedded in an elastoplastic solid and the equation for static equilibrium is solved within the context of a time-stepping method that imposes remote loading and fault slip (in a manner consistent with a fault friction law), deferring specific details to later sections. Section 3 provides details of the Drucker-Prager model for rate-independent plasticity that defines the constitutive relation (as viscoplasticity is a straight-forward extension of the associated algorithms, detailed in section 7.2). This is described in terms of the material response at a particular point in the solid, and provides a procedure for evolving stress and plastic strain given a history of total strain. Section 4 applies the results of section 3, detailing the derivation of the incremental form of the contin-

uum problem of section 2 and obtaining the governing equation solved within the time-stepping method. In section 5 we show conditions under which the resulting boundary value problem for the solid satisfies the Drucker stability condition. We also establish conservation of the incremental internal energy in the absence of nontrivial boundary conditions. Section 6 details the spatial discretization, specifically a finite difference method for variable coefficients satisfying a summation-by-parts (SBP) rule with weak enforcement of boundary conditions through the simultaneous-approximation-term (SAT) technique. The combined method will be denoted throughout the paper as SBP-SAT. We show that the semi-discrete problem using the SBP-SAT method mimics the energy balance of the continuum problem. In section 7 we describe the time stepping method for the overall problem. The solid displacement, stress, and plastic strain are updated in response to time-dependent boundary conditions obtained by updating fault slip in a manner consistent with the friction law. At each time step we solve numerically the incremental equilibrium equation for the solid using an iterative Newton procedure with the return mapping algorithm to calculate stresses consistent with the constitutive theory. The extension of the algorithms to viscoplasticity is also detailed. In section 8 we present convergence tests and comparisons with numerical solutions from a finite element code to verify our finite difference method. In section 9 we apply our method to earthquake cycle simulations, and conclude in section 10 with a discussion.

2. The Continuum Problem

In this work we assume two-dimensional antiplane shear deformation. The equation for static equilibrium in the medium is given by

$$\frac{\partial \sigma_{xy}}{\partial y} + \frac{\partial \sigma_{xz}}{\partial z} = 0, \quad (y, z) \in [-L_y, L_y] \times [0, L_z], \quad (1)$$

where σ_{xy} and σ_{xz} are the relevant components of the stress tensor σ . The constitutive relation (Hooke's law) relates stress to elastic strain through the relations

$$\sigma_{xy} = \mu(\gamma_{xy} - \gamma_{xy}^p), \quad (2a)$$

$$\sigma_{xz} = \mu(\gamma_{xz} - \gamma_{xz}^p), \quad (2b)$$

Figure 1: Schematic diagram for antiplane shear deformation where $u(t, y, z)$ is the out-of-plane displacement. We displace the sides $y = \pm L_y$ at a constant rate, with free surface conditions on the top and bottom. A frictional fault at $y = 0$ is embedded in an elastic-plastic medium.

for out-of-plane displacement $u(t, y, z)$, shear modulus μ , total engineering strains

$$\gamma_{xy} = \partial u / \partial y \quad (3a)$$

$$\gamma_{xz} = \partial u / \partial z, \quad (3b)$$

and plastic engineering strains $\gamma_{xy}^p, \gamma_{xz}^p$. Plastic deformation evolves according to a flow rule of the form

$$\dot{\gamma}_{xy}^p = \lambda P_{xy}, \quad (4a)$$

$$\dot{\gamma}_{xz}^p = \lambda P_{xz}, \quad (4b)$$

where λ is the magnitude of the plastic strain rate (a positive, scalar function of the stress), which is nonzero only when plastic deformation occurs. P_{xy}, P_{xz} are dimensionless, (generally nonlinear) functions of the stress, determine how the plastic strain rate is partitioned between different components, and specified by the particular plasticity model (*Chen and Han, 1988; Simo and Hughes, 1998*). More details are given in section 3.

A vertical, strike slip fault governed by a rate-and-state friction law lies at the interface $y = 0$ (*Dieterich, 1979; Ruina, 1983*) (see Figure 1) where we impose the condition that the jump in displacement is equal to the fault slip, Δu , namely

$$u(t, 0^+, z) - u(t, 0^-, z) = \Delta u(t, z). \quad (5)$$

In addition, we require that the components of the traction vector on the fault be equal and opposite across the interface, which, for antiplane motion, reduces to the second interface condition

$$\sigma_{xy}(t, 0^+, z) = \sigma_{xy}(t, 0^-, z). \quad (6)$$

Slow tectonic loading is imposed by displacing the remote boundaries at a constant relative rate V_p and the top and bottom boundaries are assumed to be free surfaces. We assume the solution u is anti-symmetric across the fault interface (i.e. $u(t, y, z) = -u(t, -y, z)$ for $0 \leq y \leq L_y$) so that (6) is satisfied by construction, and so we may focus on one side of the fault, namely $(y, z) \in [0, L_y] \times [0, L_z]$ (see *Erickson and Dunham (2014)* for details and a discussion on the choice of boundary conditions). For the one-sided problem the boundary conditions are thus given by

$$u(t, 0, z) = \Delta u/2, \quad (7a)$$

$$u(t, L_y, z) = V_p t/2, \quad (7b)$$

$$\sigma_{xz}(t, y, 0) = 0, \quad (7c)$$

$$\sigma_{xz}(t, y, L_z) = 0. \quad (7d)$$

In the rate-and-state friction framework, shear stress on the fault, denoted τ (and related to σ_{xy} as detailed below), is equated with frictional strength through the relation

$$\tau = \sigma_n f(V, \psi), \quad (8)$$

where

$$V = \Delta \dot{u} \quad (9)$$

denotes the slip velocity, ψ is an internal state variable, σ_n is the effective normal stress and f is a friction coefficient that takes the particular form

$$f(V, \psi) = a \sinh^{-1} \left(\frac{V}{2V_0} e^{\psi/a} \right) \quad (10)$$

(*Dieterich, 1979; Ruina, 1983*). We assume the state variable ψ evolves to the aging law form of evolution, namely

$$\frac{d\psi}{dt} = \frac{bV_0}{D_c} \left(e^{(f_0 - \psi)/b} - \frac{V}{V_0} \right). \quad (11)$$

With the aging law, state can evolve in the absence of slip, and therefore may be more suitable for modeling the interseismic period. In equations (10) and (11), a and b are dimensionless parameters quantifying the direct effect and state evolution, respectively, f_0 is a reference friction at a reference slip velocity V_0 , and D_c is the state evolution distance (Marone, 1998).

In section 7 we describe how the slip Δu is obtained in a manner consistent with the fault friction law (8), where τ is related to σ_{xy} through the following. Solving the equilibrium equation (1) provides the quasistatic stresses σ_{xy}, σ_{xz} . Since disregarding inertia entirely is known to cause slip velocity $V \rightarrow \infty$ in finite time (after which no solution exists), we incorporate the radiation damping approximation to inertia (Rice, 1993). Thus τ is defined to be

$$\tau = \sigma_{xy}(t, 0, z) - \eta_{rad}V \quad (12)$$

where $-\eta_{rad}V$ is the stress due to radiation damping and $\eta_{rad} = \mu/(2c_s)$ is half the shear-wave impedance (not to be confused with viscosity η for viscoplastic flow) for shear wave speed $c_s = \sqrt{\mu/\rho}$ and material density ρ .

3. Elastoplastic Constitutive Theory

In this section we review the Drucker-Prager elastoplastic constitutive theory that is used to evolve stress and plastic strain (in response to an imposed total strain history at a particular material point).

3.1. Drucker-Prager Plasticity

Throughout this work we assume infinitesimal strains. Hooke's law (introduced in (2) for the antiplane setting) can be expressed generally by

$$\sigma = C : (\epsilon - \epsilon^p) \quad (13)$$

where ϵ and ϵ^p are the total and plastic strain tensors. The fourth order elasticity tensor C_{ijkl} for an isotropic solid is given by

$$C_{ijkl} = K\delta_{ij}\delta_{kl} + \mu(\delta_{ik}\delta_{jl} + \delta_{il}\delta_{jk} - (2/3)\delta_{ij}\delta_{kl}), \quad (14)$$

where K is the bulk modulus. Stresses in the medium are constrained by a Drucker-Prager yield condition, see Figure 2. For rate-independent response with linear, isotropic hardening, the yield function is given by

$$F(\sigma, \gamma^p) = \bar{\tau} - (\sigma_Y + h\gamma^p), \quad (15)$$

Figure 2: The Drucker-Prager yield condition for yield function F . Elastic response occurs for states of stress that lie below the yield surface, while plastic response occurs for states on the surface. States above the yield surface are inadmissible. The slope of the line is defined by the angle of internal friction ϕ , while the y -intercept depends further on cohesion c and hardening modulus h .

where γ^p is the hardening parameter (equivalent plastic strain, defined below) and h is the hardening modulus. In this work we assume $h > 0$ is constant (we say the response is strain-softening if $h < 0$, and perfectly plastic if $h = 0$). The elastic domain in stress space is given by $\mathbb{E}_\sigma = \{(\sigma, \gamma^p) : F(\sigma, \gamma^p) \leq 0\}$ and plastic flow ensues when the yield condition

$$F(\sigma, \gamma^p) = 0 \quad (16)$$

is met. The second invariant of the deviatoric stress is

$$\bar{\tau} = \sqrt{s_{ij}s_{ij}/2} \quad (17)$$

for $s_{ij} = \sigma_{ij} - \sigma_{kk}\delta_{ij}/3$. The yield stress is given by

$$\sigma_Y = -(\sigma_{kk}/3) \sin \phi + c \cos \phi, \quad (18)$$

where c is the cohesion and ϕ is the internal friction angle. Plastic strain evolves according to the flow rule (introduced in equation (4)) given by

$$\dot{\epsilon}_{ij}^p = \lambda P_{ij}, \quad (19)$$

where $\lambda = \sqrt{2\dot{e}_{ij}^p \dot{e}_{ij}^p}$ is the deviatoric plastic strain rate for $e_{ij}^p = \epsilon_{ij}^p - \epsilon_{kk}^p \delta_{ij}/3$.
Thus

$$\gamma^p(t) = \int_0^t \lambda(s) ds, \quad (20)$$

and P_{ij} (specified in the next section) quantifies how plastic strain is distributed between different components of the plastic strain rates. The constitutive theory is closed by including the Kuhn-Tucker loading/unloading (complementarity) conditions

$$\lambda \geq 0, \quad F \leq 0, \quad \lambda F = 0, \quad (21)$$

(which ensure that plastic flow can only occur if stresses lie on the yield surface) and the consistency (persistency) condition

$$\lambda \dot{F} = 0, \quad (22)$$

so that if plastic flow occurs, the stress state must persist on the yield surface for some positive period of time.

3.2. Elastoplastic Tangent Stiffness Tensor

In rate form, Hooke's law (13) expresses stress rate in terms of total strain rate, namely

$$\dot{\sigma}_{ij} = C_{ijkl}^{ep} \dot{\epsilon}_{kl}, \quad (23)$$

where the continuum elastoplastic tangent stiffness tensor $C_{ijkl}^{ep} = C_{ijkl}^{ep}(\sigma)$ is a nonlinear function of stress. We derive this tensor following *Simo and Hughes* (1998), by first taking the time derivative of the yield function, and then using (19) and the time derivative of (20):

$$\begin{aligned} \dot{F} &= \frac{\partial F}{\partial \sigma_{ij}} \dot{\sigma}_{ij} + \frac{\partial F}{\partial \gamma^p} \dot{\gamma}^p = \frac{\partial F}{\partial \sigma_{ij}} C_{ijkl}^{ep} (\dot{\epsilon}_{kl} - \dot{e}_{kl}^p) + \frac{\partial F}{\partial \gamma^p} \dot{\gamma}^p \\ &= \frac{\partial F}{\partial \sigma_{ij}} C_{ijkl}^{ep} \dot{\epsilon}_{kl} - \lambda \left(\frac{\partial F}{\partial \sigma_{ij}} C_{ijkl}^{ep} P_{kl} - \frac{\partial F}{\partial \gamma^p} \right). \end{aligned} \quad (24)$$

Assuming that

$$\left(\frac{\partial F}{\partial \sigma_{ij}} C_{ijkl}^{ep} P_{kl} - \frac{\partial F}{\partial \gamma^p} \right) > 0, \quad (25)$$

(in order to ensure consistency with (21)-(22), see *Simo and Hughes* (1998) for more details), we can solve $\dot{F} = 0$ for λ , namely

$$\lambda = \frac{\langle \frac{\partial F}{\partial \sigma_{ij}} C_{ijkl} \dot{\epsilon}_{kl} \rangle}{\frac{\partial F}{\partial \sigma_{mn}} C_{mnop} P_{op} - \frac{\partial F}{\partial \gamma^p}}, \quad (26)$$

where the brackets denote the ramp function $\langle x \rangle = \frac{x+|x|}{2}$. Taking the time derivative of the stress and substituting in the flow rule yields

$$\dot{\sigma}_{ij} = C_{ijkl}(\dot{\epsilon}_{kl} - \lambda P_{kl}) = C_{ijkl} \left(\dot{\epsilon}_{kl} - \frac{\langle \frac{\partial F}{\partial \sigma_{mn}} C_{mnop} \dot{\epsilon}_{op} \rangle}{\frac{\partial F}{\partial \sigma_{qr}} C_{qrst} P_{st} - \frac{\partial F}{\partial \gamma^p}} P_{kl} \right), \quad (27)$$

which allows us to express the continuum elastoplastic tangent stiffness tensor

$$C_{ijkl}^{ep} = \begin{cases} C_{ijkl} & \text{if } \lambda = 0, \\ C_{ijkl} - \frac{C_{ijop} P_{op} C_{mnkl} \frac{\partial F}{\partial \sigma_{mn}}}{\frac{\partial F}{\partial \sigma_{qr}} C_{qrst} P_{st} - \frac{\partial F}{\partial \gamma^p}} & \text{if } \lambda > 0. \end{cases} \quad (28)$$

Note that C^{ep} is symmetric in the same manner as the elastic tensor given in (14) (namely, that $C_{ijkl}^{ep} = C_{jikl}^{ep} = C_{ijlk}^{ep} = C_{klij}^{ep}$), if the flow rule (19) is associative (i.e. if $P_{ij} = \frac{\partial F}{\partial \sigma_{ij}}$). For Drucker-Prager plasticity,

$$P_{ij} = s_{ij}/(2\bar{\tau}) + (\beta/3)\delta_{ij}, \quad (29)$$

where β determines the degree of plastic dilatancy. Thus the flow rule is associative only if $\beta = \sin(\phi)$.

Expression (28) is thus

$$C_{ijkl}^{ep} = \begin{cases} C_{ijkl} & \text{if } \lambda = 0, \\ C_{ijkl} - \frac{\frac{\mu^2}{\bar{\tau}^2} s_{ij} s_{kl} + \frac{\mu K}{\bar{\tau}} [\sin(\phi) s_{ij} \delta_{kl} + \beta \delta_{ij} s_{kl}] + \beta K^2 \sin(\phi) \delta_{ij} \delta_{kl}}{\mu + \beta K \sin(\phi) + h} & \text{if } \lambda > 0 \end{cases} \quad (30)$$

and associativity (symmetry of C_{ijkl}^{ep}) holds in the general case if $\beta = \sin \phi$.

4. The Governing Equation in Incremental Form

Because of the nonlinearity of the constitutive relation (2), a typical approach taken is to consider the rate form, given by (23), and posit the equilibrium equation (1) in terms of an infinitesimal displacement increment du

(Chen and Han, 1988; Simo and Hughes, 1998; Dunne and Petrinic, 2006). In this section we derive the incremental equilibrium equation as well as the specific forms of the relevant elastoplastic moduli. Note that although du is an infinitesimally small increment in the continuum setting, it is taken to be finite when the problem is discretized in time as done in section 7.

In the case of antiplane strain, the only non-zero strains are γ_{xy}, γ_{xz} . For notational purposes, we therefore denote the relevant components of the fourth-order tensor C as $C_{xyxy} = C_{11}, C_{xyxz} = C_{12}, C_{xzyx} = C_{21}$, and $C_{xzzx} = C_{22}$. We use similar notation to denote relevant components of the elastoplastic tangent stiffness tensor, C^{ep} , introduced in the previous section.

Using the rate form (23) allows us to replace (2) with an expression solely in terms of increments of stress $d\sigma$ and strain $d\gamma$, namely

$$d\sigma_{xy} = C_{11}^{ep} d\gamma_{xy} + C_{12}^{ep} d\gamma_{xz}, \quad (31a)$$

$$d\sigma_{xz} = C_{21}^{ep} d\gamma_{xy} + C_{22}^{ep} d\gamma_{xz}, \quad (31b)$$

where

$$d\gamma_{xy} = \frac{\partial du}{\partial y}, \quad d\gamma_{xz} = \frac{\partial du}{\partial z} \quad (32)$$

are the incremental total engineering strains and du is the (infinitesimal) displacement increment.

Relations (31), along with the strain-displacement relations (32) are substituted into the incremental form of the equilibrium equation (1) and produce the nonlinear equilibrium equation for du given by

$$\frac{\partial}{\partial y} \left[C_{11}^{ep} \frac{\partial du}{\partial y} + C_{12}^{ep} \frac{\partial du}{\partial z} \right] + \frac{\partial}{\partial z} \left[C_{21}^{ep} \frac{\partial du}{\partial y} + C_{22}^{ep} \frac{\partial du}{\partial z} \right] = 0. \quad (33)$$

Recall that the elastoplastic moduli $C_{11}^{ep}, C_{12}^{ep}, C_{21}^{ep}$ and C_{22}^{ep} in equation (33) depend nonlinearly on the stress. Forming the 2×2 matrix

$$\bar{C}^{ep}(\sigma) = \begin{bmatrix} C_{11}^{ep} & C_{12}^{ep} \\ C_{21}^{ep} & C_{22}^{ep} \end{bmatrix} \quad (34)$$

(matrix $\bar{C}$ is formed analogously), we derive conditions in section 5 such that $\det \bar{C}^{ep} > 0$, as is required for well-posedness.

Specified background stresses in the medium, denoted $\sigma_{xx}^0, \sigma_{yy}^0, \sigma_{zz}^0$ are depth variable (see section 9), and the initial background shear stresses are given by σ_{xy}^0 and σ_{xz}^0 . Note that from (30), antiplane deformation can activate

changes in normal stresses (for example, $d\sigma_{xx} = C_{xxxy}^{ep} d\gamma_{xy} + C_{xxxz}^{ep} d\gamma_{xz}$) unless the relevant components of the tangent stiffness tensor are zero. This scenario can be avoided with the assumption $\beta = 0$ and $\sigma_{xx}^0 = \sigma_{yy}^0 = \sigma_{zz}^0$, which we make for the rest of this work.

In this work we assume isotropic elastic moduli $C_{11} = C_{22} = \mu$, and $C_{12} = C_{21} = 0$.

For antiplane strain the specific components for the elastoplastic stiffness tensor (30) are thus

$$C_{11}^{ep} = \begin{cases} \mu & \text{if } \lambda = 0, \\ \mu - \frac{\mu\sigma_{xy}^2/\bar{\tau}^2}{1+h/\mu} & \text{if } \lambda > 0, \end{cases} \quad (35)$$

$$C_{22}^{ep} = \begin{cases} \mu & \text{if } \lambda = 0, \\ \mu - \frac{\mu\sigma_{xz}^2/\bar{\tau}^2}{1+h/\mu} & \text{if } \lambda > 0, \end{cases} \quad (36)$$

and

$$C_{12}^{ep} = C_{21}^{ep} = \begin{cases} 0 & \text{if } \lambda = 0, \\ -\frac{\mu\sigma_{xy}\sigma_{xz}/\bar{\tau}^2}{1+h/\mu} & \text{if } \lambda > 0. \end{cases} \quad (37)$$

Note that matrix $\bar{C}^{ep}$ is symmetric and in the antiplane setting, Drucker-Prager reduces to von-Mises plasticity. Equation (17) reduces to

$$\bar{\tau} = \sqrt{\sigma_{xy}^2 + \sigma_{xz}^2} \quad (38)$$

and the corresponding flow rule (19) is given by

$$\dot{\gamma}_{xy}^p = \lambda \frac{\sigma_{xy}}{\bar{\tau}}, \quad \dot{\gamma}_{xz}^p = \lambda \frac{\sigma_{xz}}{\bar{\tau}}. \quad (39)$$

The yield stress (18) reduces to

$$\sigma_Y = -(\sigma_{kk}^0/3) \sin \phi + c \cos \phi. \quad (40)$$

5. Incremental Energy Balance

We now switch from tensor notation used in previous sections to matrix/vector notation, in order to facilitate comparison with the discrete formulation we derive in the next section. We also assume, for ease of the analysis in the following sections, that the boundary conditions for the incremental problem (33) involve general boundary data dg_L, dg_R, dg_T and dg_B at the left, right, top and bottom boundaries (respectively) namely,

$$du(t, 0, z) = dg_L(t, z), \quad (41a)$$

$$du(t, L_y, z) = dg_R(t, z), \quad (41b)$$

$$C_{21}^{ep} \frac{\partial du}{\partial y} + C_{22}^{ep} \frac{\partial du}{\partial z} \Big|_{z=0} = dg_T(t, y), \quad (41c)$$

$$C_{21}^{ep} \frac{\partial du}{\partial y} + C_{22}^{ep} \frac{\partial du}{\partial z} \Big|_{z=L_z} = dg_B(t, y). \quad (41d)$$

Later, however, we outline how we specify incremental boundary conditions so as to impose fault slip, slow tectonic loading and free surface conditions, as expressed in (7).

Assuming the solution to (33) with boundary conditions (41) is sufficiently smooth, we multiply (33) by the incremental velocity $d\dot{u}$ and integrate by parts, yielding the following energy balance

$$\frac{d}{dt} dE = \int_0^{L_z} d\dot{u} d\sigma_{xy} \Big|_0^{L_y} dz + \int_0^{L_y} d\dot{u} d\sigma_{xz} \Big|_0^{L_z} dy, \quad (42)$$

where the incremental internal energy is defined by

$$dE = \frac{1}{2} \int_0^{L_y} \int_0^{L_z} dU^T \bar{C}^{ep}(\sigma) dU dy dz \quad (43)$$

for vector

$$dU = \begin{bmatrix} \partial du / \partial y \\ \partial du / \partial z \end{bmatrix}.$$

The symmetric 2×2 matrix $\bar{C}^{ep}$ has eigenvalues

$$\lambda_1, \lambda_2 = \begin{cases} \mu & \text{if } \lambda = 0, \\ \mu, h/(1 + h/\mu) & \text{if } \lambda > 0 \end{cases} \quad (44)$$

and (25) implies that $1 + h/\mu > 0$. $\bar{C}^{ep}$ is therefore positive definite for rate-independent plasticity if and only if $h > 0$ (*Horn and Johnson, 1985*). If $h < 0$, $\det(\bar{C}^{ep}) = \lambda_1 \lambda_2 \leq 0$, which results in a loss of ellipticity of the equilibrium equation (33) and a loss of solvability. This case violates Drucker's first stability postulate (requiring $dU^T \bar{C}^{ep}(\sigma) dU > 0$) and can lead to problems including loss of uniqueness of the solution (*Drucker, 1959; Jain, 1989*;

317 *Bower*, 2010). For the case $h \leq 0$, the constitutive theory therefore requires
 318 modification (through the introduction of rate dependence, for example).
 319 Thus for rate-independent plasticity, $h > 0$ is required; however, viscosity in
 320 the viscoplastic model ensures a positive definite matrix, even if $h = 0$ (see
 321 section 7.2).

322 Note that in terms of increments, the rate of change of the internal energy
 323 can be decomposed into the sum of the rate of change of the mechanical (elas-
 324 tic strain) energy and the plastic dissipation (a positive quantity), namely,

$$\frac{d}{dt}dE = \frac{d}{dt} \int_0^{L_y} \int_0^{L_z} \frac{1}{2} [dU^e]^T \bar{C} dU^e dy dz + \int_0^{L_y} \int_0^{L_z} [dU^e]^T \bar{C} d\dot{U}^p dy dz, \quad (45)$$

325 where $dU^e = dU - dU^p$, is the vector of elastic strains and the plastic strain
 326 vector is
 327

$$dU^p = \begin{bmatrix} d\gamma_{xy}^p \\ d\gamma_{xz}^p \end{bmatrix}.$$

328
 329 For simplicity in the analysis only (see *Erickson and Dunham* (2014) for
 330 details), we may take the boundary data $dg_L = dg_R = dg_T = dg_B = 0$ and
 331 show that (42) reduces to

$$\frac{d}{dt}dE = 0, \quad (46)$$

332 showing conservation of the incremental internal energy (or dissipation of the
 333 incremental mechanical energy) in the absence of source terms and nontrivial
 334 boundary conditions (i.e., in the absence of work done by body forces or
 335 surface tractions).
 336

337 6. The Spatial Discretization

338 The nonlinearities present in the governing equation (33) with boundary
 339 conditions (41) make analytical solutions difficult, if not impossible to obtain,
 340 except perhaps in certain limiting cases. SBP-SAT finite difference methods
 341 are often used, however, to obtain numerical approximations to solutions
 342 of nonlinear problems (e.g., Navier-Stokes from fluid mechanics (*Nordström*
 343 *et al.*, 2007)), although the stability analysis can be challenging and is gen-
 344 erally approached by consideration of the linearized or “frozen coefficient”
 345 problem. If the solution is sufficiently smooth (which is not guaranteed for

our problem), the linearized analysis is often enough to ensure convergence for the nonlinear problem (*Gustafsson*, 2008).

We discretize equation (33) using the second-order accurate, narrow-stencil, summation-by-parts (SBP) finite difference operators for second derivatives, originally defined in *Mattsson and Nordström* (2004) for constant coefficients, and for variable coefficients in *Mattsson* (2011). Time-dependent boundary conditions are imposed and the elastoplastic moduli C_{11}^{ep} , C_{12}^{ep} , C_{21}^{ep} and C_{22}^{ep} are nonlinear functions of the current stress state (or equivalently, of the displacement increment). We use a Newton's method with line search to solve the nonlinear equation, detailed in section 7.3. At each time step, and each iteration of Newton's method we consider the moduli as frozen, spatially variable coefficients, and use the static counterpart of the spatial discretization of the anisotropic acoustic wave equation in heterogeneous media (*Virta and Mattsson*, 2014).

We apply second-order accurate SBP operators and introduce the 2D operators by first considering one spatial dimension. The 1D domain $y \in [0, L]$ is discretized into $N_y + 1$ grid points $y_0, y_1, \dots, y_{N_y}$ with grid spacing $\Delta y = L/N_y$. First derivatives are approximated by $\frac{\partial u}{\partial y} \approx \mathbf{D}\mathbf{u}$, where $\mathbf{u} = [u_0, u_1, \dots, u_{N_y}]^T$ is the grid function and matrix $\mathbf{D} = \mathbf{H}^{-1}\mathbf{Q}$ is an $N_y + 1 \times N_y + 1$ finite difference operator. $\mathbf{H}$ and $\mathbf{Q}$ are also $N_y + 1 \times N_y + 1$ matrices and the building blocks for the SBP operators. $\mathbf{H}$ is a diagonal, positive definite quadrature matrix defining a discrete norm on the space of grid functions

$$\|\mathbf{u}\|_H^2 = \mathbf{u}^T \mathbf{H} \mathbf{u}, \quad (47)$$

and $\mathbf{Q}$ is an almost skew-symmetric matrix such that $\mathbf{Q} + \mathbf{Q}^T = \text{diag}[-1, 0, 0, \dots, 0, 1]$. The SBP operators are derived such that they mimic integration-by-parts and provide a discrete energy estimate (that mimics its continuum counterpart). Namely, the relation $\int_0^L u \frac{\partial u}{\partial y} dy = \frac{1}{2} [u^2(L) - u^2(0)]$ is obtained by integration-by-parts and is mimicked discretely by $\mathbf{u}^T \mathbf{H} (\mathbf{D}\mathbf{u}) = \frac{1}{2} \mathbf{u}^T (\mathbf{Q} + \mathbf{Q}^T) \mathbf{u} = \frac{1}{2} (u_N^2 - u_0^2)$. If $p(y)$ defines the variable coefficient, the narrow-stencil second derivative operator for variable coefficients is given by

$$\frac{\partial}{\partial y} (p(y) \frac{\partial}{\partial y}) \approx \mathbf{D}_2^p = \mathbf{H}^{-1} (-\mathbf{M}^p + \mathbf{pBS}), \quad (48)$$

where $\mathbf{B} = \text{diag}[-1, \dots, 1]$, and $\mathbf{S}$ approximates the first derivative operator on the boundary. Matrix $\mathbf{M}^p = \mathbf{D}^T \mathbf{H} \mathbf{pD} + \mathbf{R}^p$, where $\mathbf{R}^p = \frac{(\Delta y)^3}{4} (\mathbf{D}_2)^T \mathbf{C}_2 \mathbf{pD}_2$

(correcting the typographical error in equation (21) in *Erickson and Dunham* (2014)) is a positive definite damping matrix and $\mathbf{C}_2 = \text{diag}[0, 1, 1, \dots, 1, 1, 0]$ (*Mattsson, 2011*). Matrix $\mathbf{p} = \text{diag}[p(y_0), p(y_1), \dots, p(y_{N_y})]$ is a $N_y + 1 \times N_y + 1$ coefficient matrix (all coefficient matrices are denoted similarly, with bold notation).

In 2D, we discretize the domain $[0, L_y] \times [0, L_z]$ with an $N_y + 1 \times N_z + 1$ -point grid, defined by

$$y_i = i\Delta y, \quad i = 0, 1, \dots, N_y, \quad \Delta y = L_y/N_y, \quad (49a)$$

$$z_i = i\Delta z, \quad i = 0, 1, \dots, N_z, \quad \Delta z = L_z/N_z, \quad (49b)$$

where Δy and Δz are the grid spacings in each direction. Thus $u_{i,j} \approx u(y_j, z_i)$. Letting $N = (N_y + 1)(N_z + 1)$, the $N \times 1$ grid vector $\mathbf{u}$ in 2D is given by

$$\mathbf{u} = [\mathbf{u}_0^T, \mathbf{u}_1^T, \dots, \mathbf{u}_{N_y}^T] \quad (50)$$

where

$$\mathbf{u}_i = [u_{0,i}, u_{1,i}, \dots, u_{N_z,i}], \text{ for } i = 0, \dots, N_y. \quad (51)$$

The 2D variable coefficient $p(y, z)$ defined on $[0, L_y] \times [0, L_z]$ is transformed to the $N \times N$ diagonal matrix $\mathbf{p} = \text{diag}[\mathbf{p}_0^T, \mathbf{p}_1^T, \dots, \mathbf{p}_{N_y}^T]$ using analogous notation. To form the SBP finite difference operators in 2D we make use of the Kronecker product. Recall that if matrix $\mathbf{A}$ is size $p \times q$ and $\mathbf{B}$ is $r \times s$ then the Kronecker product of the two is of size $pr \times qs$ and given by

$$\mathbf{A} \otimes \mathbf{B} = \begin{bmatrix} a_{0,0}\mathbf{B} & \cdots & a_{0,N}\mathbf{B} \\ \vdots & & \vdots \\ a_{N,0}\mathbf{B} & \cdots & a_{N,N}\mathbf{B} \end{bmatrix}. \quad (52)$$

In addition, the following identities hold:

$$(\mathbf{A} \otimes \mathbf{B})(\mathbf{C} \otimes \mathbf{D}) = (\mathbf{AC}) \otimes (\mathbf{BD}), \quad (53a)$$

$$(\mathbf{A} \otimes \mathbf{B})^{-1} = (\mathbf{A}^{-1} \otimes \mathbf{B}^{-1}) \text{ if } \mathbf{A} \text{ and } \mathbf{B} \text{ are invertible,} \quad (53b)$$

$$(\mathbf{A} \otimes \mathbf{B})^T = \mathbf{A}^T \otimes \mathbf{B}^T. \quad (53c)$$

We can thus extend any 1D operator $\mathbf{P}$ to 2D (in the y and z direction, respectively) by

$$\mathbf{P}_y = (\mathbf{P} \otimes \mathbf{I}), \quad (54a)$$

$$\mathbf{P}_z = (\mathbf{I} \otimes \mathbf{P}). \quad (54b)$$

408 The first and second derivative operators in 2D are thus

$$409 \quad \frac{\partial}{\partial y} \approx \mathbf{D}_y, \quad (55a)$$

$$410 \quad \frac{\partial}{\partial z} \approx \mathbf{D}_z, \quad (55b)$$

$$411 \quad \frac{\partial}{\partial y} \left(p(y, z) \frac{\partial}{\partial y} \right) \approx \mathbf{D}_{2y}^p = \mathbf{H}_y^{-1} [-\mathbf{D}_y^T \mathbf{p} \mathbf{H}_y \mathbf{D}_y - \mathbf{R}_y^p + \mathbf{p} \mathbf{B}_y \mathbf{S}_y], \quad (55c)$$

$$412 \quad \frac{\partial}{\partial z} \left(p(y, z) \frac{\partial}{\partial z} \right) \approx \mathbf{D}_{2z}^p = \mathbf{H}_z^{-1} [-\mathbf{D}_z^T \mathbf{p} \mathbf{H}_z \mathbf{D}_z - \mathbf{R}_z^p + \mathbf{p} \mathbf{B}_z \mathbf{S}_z], \quad (55d)$$

413 where $\mathbf{R}_y^p, \mathbf{R}_z^p$ are positive definite damping matrices in 2D (see *Erickson*
414 *and Dunham* (2014) for details). The equilibrium equation (33), along with
415 boundary conditions (41), is thus discretized by

$$416 \quad \mathbf{D}_{2y}^{\mathbf{C}^{ep}} \mathbf{du} + \mathbf{D}_y \mathbf{C}_{12}^{ep} \mathbf{D}_z \mathbf{du} + \mathbf{D}_z \mathbf{C}_{21}^{ep} \mathbf{D}_y \mathbf{du} + \mathbf{D}_{2z}^{\mathbf{C}^{ep}} \mathbf{du} + \mathbf{P}_L + \mathbf{P}_R + \mathbf{P}_T + \mathbf{P}_B = \mathbf{0}, \quad (56)$$

417 where $\mathbf{du}$ is the incremental displacement grid vector, and the SAT penalty
418 vectors are given by

$$419 \quad \mathbf{P}_L = \mathbf{H}_y^{-1} (\boldsymbol{\alpha}_L + \beta \mathbf{H}_z^{-1} (-\mathbf{C}_{11}^{ep} \mathbf{S}_y - \mathbf{C}_{12}^{ep} \mathbf{D}_z)^T) \mathbf{H}_z \mathbf{E}_0 (\mathbf{du}_L - \mathbf{dg}_L) \quad (57a)$$

$$420 \quad \mathbf{P}_R = \mathbf{H}_y^{-1} (\boldsymbol{\alpha}_R + \beta \mathbf{H}_z^{-1} (\mathbf{C}_{11}^{ep} \mathbf{S}_y + \mathbf{C}_{12}^{ep} \mathbf{D}_z)^T) \mathbf{H}_z \mathbf{E}_N (\mathbf{du}_R - \mathbf{dg}_R) \quad (57b)$$

$$421 \quad \mathbf{P}_T = -\mathbf{H}_z^{-1} (\mathbf{I}_y \otimes \mathbf{E}_0) ([-\mathbf{C}_{22}^{ep} \mathbf{S}_z \mathbf{du} - \mathbf{C}_{21}^{ep} \mathbf{D}_y \mathbf{du}]_T - \mathbf{dg}_T) \quad (57c)$$

$$422 \quad \mathbf{P}_B = -\mathbf{H}_z^{-1} (\mathbf{I}_y \otimes \mathbf{E}_N) ([\mathbf{C}_{22}^{ep} \mathbf{S}_z \mathbf{du} + \mathbf{C}_{21}^{ep} \mathbf{D}_y \mathbf{du}]_B - \mathbf{dg}_B). \quad (57d)$$

423 Recall that the coefficient matrices in (56) depend nonlinearly on the stress $\boldsymbol{\sigma}$.
424 The notation $\mathbf{du}_L$ is the restriction of the grid vector $\mathbf{du}$ to the left boundary
425 and $\mathbf{du}_R, \mathbf{du}_T, \mathbf{du}_B$, are the restrictions to the right, top and bottom bound-
426 aries (respectively). Vector $\mathbf{dg}_L$ is the boundary data dg_L evaluated at the
427 grid and $\mathbf{dg}_R, \mathbf{dg}_T, \mathbf{dg}_B$ are defined analogously. Matrices $\mathbf{E}_0$ and $\mathbf{E}_N$ map
428 the restricted vectors to full-length ($N \times 1$ length) vectors (see *Erickson and*
429 *Dunham* (2014) for details). *Virta and Mattsson* (2014) derive conditions
430 on the penalty parameter β and penalty matrices $\boldsymbol{\alpha}_L$, and $\boldsymbol{\alpha}_R$ such that a
431 semi-discrete energy estimate can be obtained. Following their analysis, the
432 semi-discrete incremental internal energy $\mathbf{dE}$ (a slightly modified analog of
433 (43)) is defined

$$434 \quad \mathbf{dE} = \frac{1}{2} \mathbf{dU}^T (\mathbf{H}_y \otimes \mathbf{H}_z) \bar{\mathbf{C}}^{ep} \mathbf{dU} + \frac{1}{2} \mathbf{du}^T (\mathbf{R}_y^{\mathbf{C}^{ep}} \otimes \mathbf{H}_z) \mathbf{du} + \frac{1}{2} \mathbf{du}^T (\mathbf{H}_y \otimes \mathbf{R}_z^{\mathbf{C}^{ep}}) \mathbf{du} + U_1 + U_2. \quad (58)$$

435 In (58), vector $\mathbf{dU} = [\mathbf{D}_y \mathbf{du} \ \mathbf{D}_z \mathbf{du}]^T$, the positive-definiteness of the $2N \times$
 436 $2N$, block diagonal matrix

$$437 \quad \bar{\mathbf{C}}^{ep} = \begin{bmatrix} \mathbf{C}_{11}^{ep} & \mathbf{C}_{12}^{ep} \\ \mathbf{C}_{21}^{ep} & \mathbf{C}_{22}^{ep} \end{bmatrix} \quad (59)$$

438 follows from that of $\bar{\mathbf{C}}^{ep}$, and U_1, U_2 are positive quantities, see Appendix
 439 A. Assuming zero-boundary data, as in the continuum problem, the semi-
 440 discrete equations are shown to satisfy the energy estimate

$$441 \quad \frac{d}{dt} \mathbf{dE} \leq 0, \quad (60)$$

442 which ensures stability of the method, see Appendix A for more details. Note
 443 that for our application problems in section 9 we desire better resolution near
 444 the fault and free surface, and therefore consider a non-uniform grid spacing.
 445 In appendix A we detail the stability analysis for a grid with non-uniform
 446 spacing; the uniform grid spacing assumed in this section (to maintain flow
 447 of the discussion) is a special case.

448 7. Time Stepping

449 In this section we explain the time stepping method for the overall prob-
 450 lem. This is done by first updating slip and the state variable along the
 451 frictional fault. The update to slip, along with the remaining boundary con-
 452 ditions, generates an increment of load. Updates to the displacement, stresses
 453 and plastic strains (that occur in the volume in response to the load) are then
 454 computed.

455 We introduce a time discretization so that notationally, superscripts on
 456 a particular field imply we are considering a *finite* increment over a discrete
 457 time step. We assume the system is equilibrated at time t^n with stresses con-
 458 sistent with the constitutive theory of section 3. Slip and state variable along
 459 the fault are updated via a Runge-Kutta method with adaptive time stepping
 460 (see section 7.4 for details). These updates provide the incremental bound-
 461 ary data $\mathbf{dg}_L^{n+1}$ along the fault, which, together with $\mathbf{dg}_R^{n+1}, \mathbf{dg}_T^{n+1}, \mathbf{dg}_B^{n+1}$,
 462 correspond to an increment of load applied over the time step $dt = t^{n+1} - t^n$
 463 that drives the system to a new state. In what follows, we describe the lat-
 464 ter part update, namely, how the displacement increment and the associated

stresses and plastic strains are updated in response to the load in a manner that accounts for plastic response.

Let the discrete equilibrium equation (56)-(57) be denoted $\mathcal{E}(\mathbf{d}\boldsymbol{\sigma}) = \mathbf{b}$ where vector $\mathbf{b}$ stores the incremental boundary data. At t^{n+1} we wish to obtain both stress and displacement increments that satisfy

$$\mathcal{E}(\mathbf{d}\boldsymbol{\sigma}^{n+1}) = \mathbf{b}^{n+1} \quad (61)$$

and are consistent with the constitutive theory of section 3, where $\mathbf{d}\boldsymbol{\sigma}^{n+1}$ is related to the displacement increment $\mathbf{d}\mathbf{u}^{n+1}$ through a discrete form of constitutive relation (31) (which we define shortly) and the discretized strain-displacement relations (32).

To obtain the displacement, stresses and strains at time t^{n+1} we first apply a backward-Euler discretization to the flow rule (19) and equivalent plastic strain

$$\gamma_{xy}^{p,n+1} = \gamma_{xy}^{p,n} + \mathbf{d}\lambda^{n+1} \frac{\sigma_{xy}^{n+1}}{\bar{\tau}^{n+1}} \quad (62a)$$

$$\gamma_{xz}^{p,n+1} = \gamma_{xz}^{p,n} + \mathbf{d}\lambda^{n+1} \frac{\sigma_{xz}^{n+1}}{\bar{\tau}^{n+1}}, \quad (62b)$$

$$\gamma^{p,n+1} = \gamma^{p,n} + \mathbf{d}\lambda^{n+1}, \quad (62c)$$

where $\mathbf{d}\lambda^{n+1} = \lambda^{n+1} dt$. A direct linearization of this discretization implies an associated discrete, incremental form of the constitutive relation given by

$$\mathbf{d}\boldsymbol{\sigma}_{ij}^{n+1} = \mathcal{C}_{ijkl}^{ep}(\boldsymbol{\sigma}^{n+1}) \mathbf{d}\boldsymbol{\epsilon}_{kl}^{n+1} \quad (63)$$

where $\mathcal{C}^{ep}$ is the *consistent* tangent stiffness tensor (and a function of the stress at the end of the time step), derived in the next section. The fully discrete equilibrium equation can thus be expressed

$$\mathcal{E}(\mathcal{C}^{ep}(\boldsymbol{\sigma}^{n+1}) \mathbf{d}\mathbf{u}^{n+1}) = \mathbf{b}^{n+1}, \quad (64)$$

and is a nonlinear function of $\mathbf{d}\mathbf{u}^{n+1}$.

To solve (64) we proceed via a Newton-type method which utilizes the partial derivative

$$\frac{\partial \mathcal{E}}{\partial \mathbf{d}\mathbf{u}^{n+1}} = \frac{\partial \mathcal{E}}{\partial \mathbf{d}\boldsymbol{\sigma}_{ij}^{n+1}} \mathcal{C}_{ijkl}^{ep}(\boldsymbol{\sigma}^{n+1}) \frac{\partial \mathbf{d}\boldsymbol{\epsilon}_{kl}^{n+1}}{\partial \mathbf{d}\mathbf{u}^{n+1}} \quad (65)$$

and incorporates the consistent tangent stiffness tensor. We set iteration index $k = 0$ and compute an initial, elastic guess $\mathbf{du}^{n+1,(k)}$ to the displacement increment, obtained by assuming $\mathcal{C}^{ep} = \mathbf{C}$ and solving (64). Consistent stresses $\boldsymbol{\sigma}^{n+1,(k)}$ associated with $\mathbf{du}^{n+1,(k)}$ are obtained from the *return mapping algorithm* which is based on the backward Euler discretization (62), and detailed in the next section. Deferring specific details until section 7.4, if the new, consistent stress state satisfies equilibrium, then the final fields are those at iteration k , and the process is considered done.

If equilibrium is not satisfied, however, the displacement increment $\mathbf{du}^{n+1,(k)}$ must be adjusted (and thus adjustments to the stress and plastic strains must be made).

The displacement increment is updated by solving (64) via an iterative Newton-type method that solves the *linearized* equilibrium problem

$$\mathcal{E}(\mathcal{C}^{ep}(\boldsymbol{\sigma}^{n+1,(k)})\mathbf{du}^{n+1,(k+1)}) = \mathbf{b}^{n+1}. \quad (66)$$

and the return mapping algorithm provides associated consistent stresses $\boldsymbol{\sigma}^{n+1,(k+1)}$ (Simo and Hughes, 1998; de Souza Neto et al., 2008). This iterative procedure continues until equilibrium has been satisfied with an appropriate convergence criterion met (see section 7.3). The displacement $\mathbf{u}^{n+1} = \mathbf{u}^n + \mathbf{du}^{n+1}$ can then be formed from the converged value of the finite increment $\mathbf{du}^{n+1}$.

7.1. The Return Mapping Algorithm

Within the Newton iteration described in the previous section, the finite displacement increment $\mathbf{du}^{n+1,(k)}$ is obtained and stresses consistent with the plastic constitutive theory must be updated (Simo and Hughes, 1998). In this section we describe how to obtain $\boldsymbol{\sigma}^{n+1,(k)}$. First, the strains associated with $\mathbf{du}^{n+1,(k)}$ are computed

$$\gamma_{xy}^{n+1,(k)} = \gamma_{xy}^n + \mathbf{d}\gamma_{xy}^{n+1,(k)}, \quad (67a)$$

$$\gamma_{xz}^{n+1,(k)} = \gamma_{xz}^n + \mathbf{d}\gamma_{xz}^{n+1,(k)}, \quad (67b)$$

and allow us to compute the elastic trial state (denoted with asterisk *)

$$\gamma^{*,p,n+1,(k)} = \gamma^{p,n}, \quad (68a)$$

$$\sigma_{xz}^{*,n+1,(k)} = \mu(\gamma_{xz}^{n+1,(k)} - \gamma_{xz}^{p,n}) = \sigma_{xz}^n + \mu\mathbf{d}\gamma_{xz}^{n+1,(k)}, \quad (68b)$$

$$\sigma_{xy}^{*,n+1,(k)} = \mu(\gamma_{xy}^{n+1,(k)} - \gamma_{xy}^{p,n}) = \sigma_{xy}^n + \mu\mathbf{d}\gamma_{xy}^{n+1,(k)}, \quad (68c)$$

524 assuming no additional plastic strain has accrued over the time step.

525 The final stress state at time t^{n+1} must satisfy $F \leq 0$, where the yield
 526 function is defined in (15) for yield stress (40). If the elastic trial stresses sat-
 527 isfy $F \leq 0$, then they are accepted as the final stresses. If the trial stresses lie
 528 outside the yield surface ($F > 0$), however, they are be “mapped back” onto
 529 the yield surface by adjusting the plastic strains so that $F(\boldsymbol{\sigma}^{n+1}, (k), \boldsymbol{\gamma}^{p,n+1,(k)}) =$
 530 0 is satisfied (*Simo and Hughes*, 1998).

531 Substituting equations (62a-b) into (68b-c) yields

$$532 \quad \sigma_{xy}^{*,n+1} = \sigma_{xy}^{n+1} (1 + \mu d\lambda^{n+1} / \bar{\tau}^{n+1}) \quad (69a)$$

$$533 \quad \sigma_{xz}^{*,n+1} = \sigma_{xz}^{n+1} (1 + \mu d\lambda^{n+1} / \bar{\tau}^{n+1}). \quad (69b)$$

534 From (69) we calculate

$$535 \quad \begin{aligned} \bar{\tau}^{*,n+1} &= \sqrt{(\sigma_{xy}^{*,n+1})^2 + (\sigma_{xz}^{*,n+1})^2} \\ 536 \quad &= \bar{\tau}^{n+1} + \mu d\lambda^{n+1}. \end{aligned} \quad (70)$$

537 Re-arranging (70), noting that $F(\boldsymbol{\sigma}^{n+1}, \boldsymbol{\gamma}^{p,n+1}) = 0$, and substituting in (62c)
 538 yields the plastic consistency condition

$$539 \quad d\lambda^{n+1} = F(\boldsymbol{\sigma}^{*,n+1}, \boldsymbol{\gamma}^{*,p,n+1}) / (h + \mu), \quad (71)$$

540 where $\boldsymbol{\gamma}^{*,p,n+1}$ is given by (68c). Finally, solving (69) for σ_{xy}^{n+1} and σ_{xz}^{n+1}
 541 yields

$$542 \quad \sigma_{xy}^{n+1,(k)} = \frac{\sigma_{xy}^{*,n+1,(k)}}{1 + \mu d\lambda^{n+1,(k)} / \bar{\tau}^{n+1,(k)}} = \frac{\sigma_{xy}^{*,n+1,(k)} (\bar{\tau}^{*,n+1,(k)} - \mu d\lambda^{n+1,(k)})}{\bar{\tau}^{*,n+1,(k)}} \quad (72a)$$

$$543 \quad \sigma_{xz}^{n+1,(k)} = \frac{\sigma_{xz}^{*,n+1,(k)}}{1 + \mu d\lambda^{n+1,(k)} / \bar{\tau}^{n+1,(k)}} = \frac{\sigma_{xz}^{*,n+1,(k)} (\bar{\tau}^{*,n+1,(k)} - \mu d\lambda^{n+1,(k)})}{\bar{\tau}^{*,n+1,(k)}} \quad (72b)$$

544 which expresses the final stress state entirely in terms of the computed elastic
 545 trial stresses.

546 The consistent elastoplastic tangent stiffness tensor $\mathcal{C}_{ijkl}^{ep}$ in (64) is ob-
 547 tained by a linearization of the return-mapping algorithm. We derive these
 548 consistent moduli in Appendix B, with specific components (ommitting su-
 549 perscripts $n+1$) given by (bold face notation is not used as these moduli are
 550 derived independently of a spatial discretization)

$$551 \quad \mathcal{C}_{11}^{ep} = \begin{cases} \mu & \text{if } \lambda = 0, \\ \mu - \frac{\mu \sigma_{xy}^2 / \bar{\tau}^2}{1 + h/\mu} - \frac{d\lambda \mu^2}{\bar{\tau}} \left[1 - \left(\frac{\sigma_{xy}}{\bar{\tau}} \right)^2 \right] & \text{if } \lambda > 0, \end{cases} \quad (73)$$

$$\mathcal{C}_{22}^{ep} = \begin{cases} \mu & \text{if } \lambda = 0, \\ \mu - \frac{\mu\sigma_{xz}^2/\bar{\tau}^2}{1+h/\mu} - \frac{d\lambda\mu^2}{\bar{\tau}} \left[1 - \left(\frac{\sigma_{xz}}{\bar{\tau}} \right)^2 \right] & \text{if } \lambda > 0, \end{cases} \quad (74)$$

and

$$\mathcal{C}_{12}^{ep} = \mathcal{C}_{21}^{ep} = \begin{cases} 0 & \text{if } \lambda = 0, \\ -\frac{\mu\sigma_{xy}\sigma_{xz}/\bar{\tau}^2}{1+h/\mu} - \frac{d\lambda\mu^2}{\bar{\tau}} \left[1 - \frac{\sigma_{xy}\sigma_{xz}}{\bar{\tau}^2} \right] & \text{if } \lambda > 0, \end{cases} \quad (75)$$

which agree with the continuum moduli in the limit that $d\lambda \rightarrow 0$.

It has been shown for many problems that using the consistent tangent moduli (73)-(75) with discretization (64) (to compute numerical solutions to (33)) then the quadratic convergence rate typical of Newton-type iterative methods is achieved. This rate of convergence is often lost, however, if the continuum tangent moduli (35)-(37) are used instead (*Simo and Taylor*, 1985). In our application problems we thus use the consistent elastoplastic moduli and leave the comparison of Newton convergence results to future work.

7.2. Extension to Viscoplasticity

Classical Perzyna viscoplasticity (*Perzyna*, 1966, 1971) is obtained from rate-independent plasticity by replacing the yield condition (16) with $F(\boldsymbol{\sigma}, \boldsymbol{\gamma}^p) = \eta \boldsymbol{\lambda}$, where $\eta > 0$ is the viscosity.

A viscoplastic response alters the return mapping algorithm in the previous section through the following: If the computed elastic trial stresses are such that $F(\boldsymbol{\sigma}^{*,n+1}, \boldsymbol{\gamma}^{*,p,n+1}) > 0$, then equations (70) and (71) are replaced with

$$\bar{\tau}^{*,n+1} = \bar{\tau}^{n+1} + \mu \frac{F^{n+1}}{\eta} dt \quad (76)$$

and

$$d\boldsymbol{\lambda}^{n+1} = F(\boldsymbol{\sigma}^{*,n+1}, \boldsymbol{\gamma}^{*,p,n+1})/(\eta/dt + h + \mu). \quad (77)$$

The consistent elastoplastic tangent moduli (73)-(75) can also be derived from linearizing the return-mapping algorithm (see Appendix B), yielding

$$\mathcal{C}_{11}^{ep} = \begin{cases} \mu & \text{if } \boldsymbol{\lambda} = 0, \\ \mu - \frac{\mu\sigma_{xy}^2/\bar{\tau}^2}{\frac{\eta/\mu}{dt} + 1 + h/\mu} - \frac{d\lambda\mu^2}{\bar{\tau}} \left[1 - \left(\frac{\sigma_{xy}}{\bar{\tau}} \right)^2 \right] & \text{if } \boldsymbol{\lambda} > 0, \end{cases} \quad (78)$$

$$\mathcal{C}_{22}^{ep} = \begin{cases} \mu & \text{if } \lambda = 0, \\ \mu - \frac{\mu\sigma_{xz}^2/\bar{\tau}^2}{\frac{\eta/\mu}{dt} + 1 + h/\mu} - \frac{d\lambda\mu^2}{\bar{\tau}} \left[1 - \left(\frac{\sigma_{xz}}{\bar{\tau}} \right)^2 \right] & \text{if } \lambda > 0, \end{cases} \quad (79)$$

577 and

$$\mathcal{C}_{12}^{ep} = \mathcal{C}_{21}^{ep} = \begin{cases} 0 & \text{if } \lambda = 0, \\ -\frac{\mu\sigma_{xy}\sigma_{xz}/\bar{\tau}^2}{\frac{\eta/\mu}{dt} + 1 + h/\mu} - \frac{d\lambda\mu^2}{\bar{\tau}} \left[1 - \frac{\sigma_{xy}\sigma_{xz}}{\bar{\tau}^2} \right] & \text{if } \lambda > 0. \end{cases} \quad (80)$$

578 Note that for a fixed η , if $dt \rightarrow 0$, the consistent elastoplastic moduli (78) -
579 (80) approach the elastic moduli. Furthermore, for $\eta > 0$, we can take $h = 0$
580 and still guarantee that $\bar{\mathcal{C}}^{ep}$ is positive definite.

581 7.3. Newton Iteration with Return-Mapping

582 We let $k = 0$, $\mathbf{du}^{n+1,(k)}$ be the initial (elastic) guess for the displacement
583 increment $\mathbf{du}^{n+1}$, and iterate as follows.

584 Step 1: Compute the strain increments

$$585 \quad \mathbf{d}\gamma_{xy}^{n+1,(k)} = \mathbf{D}_y \mathbf{du}^{n+1,(k)}, \quad (81a)$$

$$586 \quad \mathbf{d}\gamma_{xz}^{n+1,(k)} = \mathbf{D}_z \mathbf{du}^{n+1,(k)}. \quad (81b)$$

587 Step 2: Compute the elastic trial state and use the return mapping algorithm
588 to obtain the consistent stresses $\sigma_{xy}^{n+1,(k)}$, $\sigma_{xz}^{n+1,(k)}$ and plastic strain $\gamma^{p,n+1,(k)}$.

589 Step 3: Check if equilibrium is sufficiently satisfied. That is, check if a
590 stopping criterion is met, for example, $\|\mathcal{E}(\mathcal{C}^{ep}(\sigma^{n+1,(k)})\mathbf{du}^{n+1,(k)}) - \mathbf{b}^{n+1}\| <$
591 tol , where tol is a specified tolerance. If so, set $\mathbf{u}^{n+1} = \mathbf{u}^n + \mathbf{du}^{n+1,(k)}$,
592 the remaining fields are those at iteration (k) , and the Newton iteration
593 is complete. Otherwise set $k = k + 1$, solve $\mathcal{E}(\mathcal{C}^{ep}(\sigma^{n+1,(k)})\mathbf{du}^{n+1,(k+1)}) =$
594 $\mathbf{b}^{n+1}$ for $\mathbf{du}^{n+1,(k+1)}$ and return to step 1, iterating until the Newton method
595 converges and equilibrium is met.

596 7.4. Time Stepping Method

597 In this section we provide details of time stepping for the overall prob-
598 lem, which includes details of the update to slip and the state variable along
599 the fault, and provides an initial guess for the off-fault fields. As stated in
600 section 2, rate-and-state friction, as used in our algorithm, provides the set
601 of differential equations (9)-(11) that are used to evolve the fault boundary
602 displacement (i.e., fault slip). We modify the method from *Erickson and*
603 *Dunham* (2014) in order to incorporate off-fault plasticity. Bold-face type is

again used to denote spatially discrete quantities. We assume the body is equilibrated (with consistent stresses) at time t^n and that $\mathbf{V}^n$ and $\boldsymbol{\psi}^n$ are known. The following time-stepping method is illustrated in the context of a forward Euler step, but we use Matlab's adaptive, fourth order Runge-Kutta method with a relative tolerance of 10^{-7} .

Step 1. Update slip and state on the fault by explicitly integrating

$$\Delta \mathbf{u}^{n+1} = \Delta \mathbf{u}^n + dt \mathbf{V}^n \quad (82a)$$

$$\boldsymbol{\psi}^{n+1} = \boldsymbol{\psi}^n + dt G(\mathbf{V}^n, \boldsymbol{\psi}^n). \quad (82b)$$

Step 2. Set the boundary data in (41):

$$\begin{aligned} \mathbf{d}\mathbf{g}_L^{n+1} &= dt \mathbf{V}^n / 2, \\ \mathbf{d}\mathbf{g}_R^{n+1} &= dt V_p / 2, \\ \mathbf{d}\mathbf{g}_T^{n+1} &= \mathbf{d}\mathbf{g}_B^{n+1} = 0, \end{aligned}$$

form $\mathbf{b}^{n+1}$ and solve for an elastic increment $\mathbf{du}^{n+1,(0)}$; i.e., take $\mathcal{C}^{ep} = \mathbf{C}$ and solve the discrete equation (64).

Step 3. Correct the initial elastic guess $\mathbf{du}^{n+1,(0)}$ by iterating following the Newton procedure in section 7.3 until convergence is reached, thus obtaining $\mathbf{u}^{n+1}, \boldsymbol{\sigma}_{xy}^{n+1}, \boldsymbol{\sigma}_{xz}^{n+1}, \boldsymbol{\gamma}_{xy}^{p,n+1}, \boldsymbol{\gamma}_{xz}^{p,n+1}, \boldsymbol{\gamma}^{p,n+1}$.

Step 4. Compute the shear stress $\boldsymbol{\tau}_{qs}^{n+1} = \boldsymbol{\sigma}_{xy}^{n+1}|_{y=0}$ on the fault.

Step 5. Equate shear stress with frictional strength $\boldsymbol{\tau}_{qs}^{n+1} - \eta_{rad} \mathbf{V}^{n+1} = \boldsymbol{\sigma}_n f(\mathbf{V}^{n+1}, \boldsymbol{\psi}^{n+1})$ and solve for the updated slip velocity $\mathbf{V}^{n+1}$ (solved using a local, safe-guarded Newton method) and return to step 1.

8. Convergence Tests and Comparison with Finite Element Solution

We conduct two studies to verify our numerical method. The first study is a convergence test of our spatial discretization and time-stepping for an elastic problem; the second study is a comparison test with a finite element solution for the same plasticity model.

For the first study we proceed with the method of manufactured solutions and show that our numerical solution is converging to the exact solution at the correct rate (*Roache*, 1998). The nonlinearity introduced by plasticity makes this procedure difficult, thus we solve the anisotropic elastic version by assuming that the elastoplastic moduli do not vary with stress or time, but rather in space only. We want to check that our incremental procedure will provide a numerical approximation to the exact solution to the non-incremental equilibrium equation

$$\frac{\partial}{\partial y} \left[C_{11}^{ep}(y, z) \frac{\partial u}{\partial y} + C_{12}^{ep}(y, z) \frac{\partial u}{\partial z} \right] + \frac{\partial}{\partial z} \left[C_{21}^{ep}(y, z) \frac{\partial u}{\partial y} + C_{22}^{ep}(y, z) \frac{\partial u}{\partial z} \right] = 0, \quad (83)$$

where the moduli in (83) are known functions of space. Let the exact displacement (denoted with a hat) to (83) be that given in *Erickson and Dunham* (2014), namely

$$\hat{u}(t, y, z) = \frac{\delta}{2} K(t) \Phi(y, z) + \frac{V_p t}{2} [1 - \Phi(y, z)] + \frac{\tau^\infty}{\mu} y, \quad (84)$$

which provides the exact (elastic) stresses (also denoted with hats)

$$\hat{\sigma}_{xy} = C_{11}^{ep}(y, z) \partial \hat{u} / \partial y + C_{12}^{ep}(y, z) \partial \hat{u} / \partial z \quad (85a)$$

$$\hat{\sigma}_{xz} = C_{21}^{ep}(y, z) \partial \hat{u} / \partial y + C_{22}^{ep}(y, z) \partial \hat{u} / \partial z. \quad (85b)$$

Appropriate source terms are added to (83) so that $\hat{u}$ is indeed the solution. In the construction of the exact solution (84), $K(t)$ controls the time-dependency of the solution, δ is the total slip that occurs during the event, τ^∞ is a parameter that defines the remote stress, and Φ describes the spatial dependency of the solution. The specific forms are given by

$$\delta = V_p \bar{t} + V_{\min} \bar{t}, \quad (86a)$$

$$K(t) = \frac{1}{\pi} \left[\tan^{-1} \left(\frac{t - \bar{t}}{t_w} \right) + \frac{\pi}{2} \right] + \frac{V_{\min}}{\delta}, \quad (86b)$$

$$\Phi(y, z) = \frac{H(H + y)}{(H + y)^2 + z^2}, \quad (86c)$$

where $\bar{t}$ denotes the event time, t_w denotes the time scale over which the event occurs, $V_{\min}$ defines a minimum slip velocity throughout the simulation, and

H defines a locking depth. For the elastic moduli, we assume the following forms

$$C_{11}^{ep} = \mu - \frac{\mu c_1(y, z)^2 / |c|^2}{1 + h/\mu}, \quad (87a)$$

$$C_{22}^{ep} = \mu - \frac{\mu c_2(y, z)^2 / |c|^2}{1 + h/\mu}, \quad (87b)$$

$$C_{12}^{ep} = C_{21}^{ep} = -\frac{\mu c_1(y, z) c_2(y, z) / |c|^2}{1 + h/\mu}, \quad (87c)$$

where

$$c_1(y, z) = \frac{H_1^2}{H_1^2 + z^2} \frac{L_1^2}{L_1^2 + y^2}, \quad (88a)$$

$$c_2(y, z) = \frac{H_2^2}{H_2^2 + z^2} \frac{L_2^2}{L_2^2 + y^2} \quad (88b)$$

and $|c|^2 = c_1^2 + c_2^2$. Thus the moduli form a symmetric, positive definite matrix $\bar{C}^{ep}$ if $h > 0$. The exact slip along the fault is

$$\Delta \hat{u}(t, z) = 2\hat{u}(t, 0, z) = \delta K(t) \Phi(0, z) + V_p t [1 - \Phi(0, z)], \quad (89)$$

with slip velocity

$$\hat{V}(t, z) = \frac{\partial u^*}{\partial t} \Big|_{y=0^+} - \frac{\partial u^*}{\partial t} \Big|_{y=0^-} = \delta K'(t) \Phi(y, z) + V_p [1 - \Phi(0, z)]. \quad (90)$$

Lastly, since $\hat{\tau}(t, z) = \hat{\sigma}_{xy}(t, 0, z)$, we can solve (8) for the exact state variable

$$\hat{\psi} = a \ln \left[\frac{2V_0}{\hat{V}} \sinh \left(\frac{\hat{\tau} - \eta_{rad} \hat{V}}{\sigma_n a} \right) \right] \quad (91)$$

which implies that a source term must also be added to state evolution

$$\dot{\psi} = G(V, \psi) + s(t, z) \quad (92)$$

where

$$s = \dot{\hat{\psi}} - G(\hat{V}, \hat{\psi}). \quad (93)$$

All parameter values used in the convergence tests are given in Table 1. At the end of the simulation ($t_f = 70$ years), we compute the relative error

Table 1: Parameters used in the manufactured solution convergence tests.

Parameter	Definition	Value
L_z	fault length	24 km
L_y	off-fault domain length	24 km
ℓ_z	z-length scale for coordinate transform	5 km
ℓ_y	y-length scale for coordinate transform	5 km
H	locking depth	14 km
L_1	y-length scale for c_1	5 km
H_1	z-length scale for c_1	6 km
L_2	y-length scale for c_2	4 km
H_2	z-length scale for c_2	5 km
ρ	density	2670 kg/m ³
μ	shear modulus	30 GPa
h	hardening modulus	30 GPa
σ_n	normal stress on fault	50 MPa
τ^∞	remote shear stress	40 MPa
t_f	final simulation time	70 years
$\bar{t}$	event nucleation time	35 years
t_w	timescale for event duration	10 s
a	rate-and-state parameter	0.015
b	rate-and-state parameter	0.02
D_c	critical slip distance	0.4 m
V_p	plate rate	10 ⁻⁹ m/s
V_0	reference velocity	10 ⁻⁶ m/s
f_0	reference friction coefficient	0.6

Table 2: Relative error in the discrete $\mathbf{H}$ - and energy-norms with $N = N_x = N_y$. The rate of convergence approaches 2, as expected for a method with second-order accuracy.

N	$\text{Error}_H(h)$	Rate	$\text{Error}_E(h)$	Rate
2^4	1.030×10^{-3}	—	1.236×10^{-3}	—
2^5	2.867×10^{-4}	1.845	3.514×10^{-4}	1.814
2^6	7.433×10^{-5}	1.947	9.242×10^{-5}	1.927
2^7	1.883×10^{-5}	1.981	2.360×10^{-5}	1.970
2^8	4.741×10^{-6}	1.990	5.967×10^{-6}	1.984

between the exact and the numerical approximation in both the discrete H -norm and the energy-norm, defined by

$$\text{Error}_H(h) = \|\mathbf{u} - \hat{\mathbf{u}}\|_H / \|\hat{\mathbf{u}}\|_H \quad (94a)$$

$$\text{Error}_E(h) = \|\mathbf{u} - \hat{\mathbf{u}}\|_E / \|\hat{\mathbf{u}}\|_E \quad (94b)$$

where

$$\|\mathbf{u}\|_H^2 = \sum_{i=1}^M \|\mathbf{d}\mathbf{u}_i\|_H^2 \quad (95a)$$

$$\|\mathbf{u}\|_E^2 = \sum_{i=1}^M \mathbf{d}\mathbf{E}_i \quad (95b)$$

where $\|\mathbf{d}\mathbf{u}\|_H^2 = (\mathbf{d}\mathbf{u})^T (\mathbf{H}_y \otimes \mathbf{H}_z) (\mathbf{d}\mathbf{u})$, M is the number of adaptive, Runge-Kutta time steps and $\mathbf{d}\mathbf{E}$ is the incremental internal energy defined by (58). Table 2 shows that we are achieving second-order convergence, as expected.

Because this first verification study confirmed convergence for an anisotropic elastic problem, the purpose of the next study is to validate our results with plasticity. For the second validation study, we compare results of the solution to a boundary value problem subject to Drucker-Prager plasticity. Results from our finite difference code are compared to those from a finite element solution using the OpenSees Software Framework (Mazzoni *et al.*, 2009) and available at <http://opensees.berkeley.edu>.

We want to confirm that our incremental approach using equation (33) (in the context of the time stepping method outlined in the previous section) solves the non-incremental form of the governing equation (1), on the domain

(y, z) ∈ [0, L] × [0, L] with boundary conditions given by

$$u(0, z) = 0 \quad (96a)$$

$$u(L, z) = g(z) \quad (96b)$$

$$\sigma_{xz}(y, 0) = 0 \quad (96c)$$

$$\sigma_{xz}(y, L) = 0. \quad (96d)$$

Boundary data $g(z)$ and all parameter values are listed in Table 3. Stresses are subject to the Drucker-Prager yield condition (15) with constant yield stress σ_Y . We assume an equal grid spacing $\Delta = \Delta y = \Delta z$ of both 1 km ($N_y = N_z = 24$) and 200 m ($N_y = N_z = 120$). Figure 3 shows solutions from the finite difference solution to the plastic boundary value problem with $\Delta = 200$ m, along with the elastic counterpart of the same boundary value problem, in order to illustrate the differences between the two material models. Figure 3(a-c) show the displacement and two relevant stress components of the plastic solution (in dashed lines) and the elastic solution (solid lines) at different z -values. Figure 3(d-f) are the equivalent fields at various y -values. Although plasticity mildly affects the displacement field, the stresses are significantly reduced in amplitude, particularly near $x = 24$ km. Fig. 4 compares contours from the finite difference and finite element solution with $\Delta = 1$ km. The finite difference solution is plotted in solid colors, while the finite element solution is plotted with black circles. The displacement fields in Fig. 4(a-b) are quite similar, but error is visible in the computed stresses, particularly in Fig. 4(d) near $y = 24$ km. This error is visibly decreased when mesh refining, as shown in Figure 5. Absolute and relative errors between the computed fields using the two methods are denoted by $\text{err}_u^a = \|\mathbf{u}^{FD} - \mathbf{u}^{FE}\|_2$ and $\text{err}_u^r = \|\mathbf{u}^{FD} - \mathbf{u}^{FE}\|_2 / \|\mathbf{u}^{FE}\|_2$, respectively, and errors for other fields are defined analogously. Results shown in Table 4 suggest the two methods produce similar results.

9. Application

We are interested in how changes in viscosity, isotropic hardening and cohesion affect features of the earthquake cycle. We find that all three parameters influence the magnitude and off-fault extent of plastic strain, and that in all cases, plasticity affects the amount of slip on the fault in the shallow sub-surface during each rupture. We use the combined spatial discretization and time-stepping method detailed in previous sections to sim-

Table 3: Parameters used in antiplane plastic case for comparison of FDM and FEM.

Parameter	Definition	Value
L_z	fault length	24 km
L_y	off-fault domain length	24 km
μ	shear modulus	32.038 GPa
ρ	material density	2670 kg/m ³
$g(z)$	right boundary condition	$-\cos(\pi z/12) + 1$ (m)
σ_Y	yield stress	4 MPa
ϕ	angle of internal friction	0
h	hardening modulus	32.038 GPa

Table 4: Absolute and relative error between our finite difference solution and that obtained from the finite element code in the discrete L^2 -norm for $N_y = N_z = 24, 120$.

N	err_u^a	err_u^r	$\text{err}_{\sigma_{xy}}^a$	$\text{err}_{\sigma_{xy}}^r$	$\text{err}_{\sigma_{xx}}^a$	$\text{err}_{\sigma_{xx}}^r$
24	1.06×10^0	3.27×10^{-2}	1.72×10^0	3.72×10^{-2}	4.76×10^{-2}	3.22×10^{-2}
120	9.87×10^{-2}	3.04×10^{-3}	1.92×10^{-1}	4.14×10^{-3}	3.81×10^{-3}	2.70×10^{-4}

ulate multiple earthquake cycles with off-fault plasticity. The fault is governed by rate-and-state friction with depth-variable parameters a and b (see Fig. 6a). Where $a - b < 0$ defines the velocity-weakening (seismogenic) zone, below which the fault creeps interseismically. As an initial study, we assume that the effective normal stresses in the medium are given by $\sigma_{xx}^0 = \sigma_{yy}^0 = \sigma_{zz}^0 = -(\rho - \rho_w)gz + P_{atm}$ where ρ_w is the density of water, g is the acceleration due to gravity and atmospheric pressure P_{atm} is set to 0.1 MPa. The yield stress (15) is thus linearly increasing with depth, see Figure 6b. We assume the pore-pressure in the fault is higher than in the surrounding rock so that although the effective stresses off the fault are depth-variable, effective normal stress on the fault is constant below some depth, see Figure 6b (Rice, 1992). Fixing the internal friction parameter ϕ sets the slope of the yield stress and the yield stress at Earth's surface can be increased or decreased by changing the value of the cohesion c , which we assume is constant with depth. We vary cohesion between 40 and 50 MPa, which are reasonable depth-averaged values of those derived from Hoek-Brown parameters for many rock strength models (Roten et al., 2016). The parameters we use in our simulations are given in Table 5.

To determine grid spacing for our application simulations, Ranjith (2008)

Table 5: Parameters used in application simulations.

Parameter	Definition	Value
L_z	fault length	24 km
L_y	off-fault domain length	24 km
μ	shear modulus	36 GPa
ρ	density	2800 kg/m ³
c_s	shear wave speed	3.586 km/s
ρ_w	density of water	1000 kg/m ³
σ_n	normal stress on fault	depth-variable
τ^∞	remote shear stress	10 ⁻⁷ MPa
a	rate-and-state parameter	depth-variable
b	rate-and-state parameter	depth-variable
D_c	critical slip distance	8 mm
V_p	plate rate	10 ⁻⁹ m/s
V_0	reference velocity	10 ⁻⁶ m/s
f_0	reference friction coefficient	0.6
c	cohesion	variable
h	hardening modulus	variable
ϕ	internal friction angle	arctan(0.6)

Figure 3: Contours of solution to (1) with boundary conditions (96) for elastic (solid lines) and plastic (dashed lines) material response. (a)-(b) displacement and (c)-(f) stress components. Plastic effects are seen most prominently in the stress contours which are reduced due to the yield condition.

found that for antiplane sliding between two anisotropic elastic materials, instability occurs for wave numbers below the critical wave number

$$k_{cr} = \frac{2(b-a)\sigma_n}{D_c \mu^*}, \quad (97)$$

Figure 4: Contours of solution to (1) with boundary conditions (96) for plastic material response using the finite difference method (solid lines) and the finite element solution (black dots). (a)-(b) displacement and (c)-(f) stress components, with $N_y = N_z = 24$ points.

where

$$\mu^* = \sqrt{\det(\bar{C}^{ep})}. \quad (98)$$

Thus the length scale

$$h^* = \frac{2\pi}{k_{cr}} = \frac{\pi D_c \mu^*}{(b-a)\sigma_n} \quad (99)$$

Figure 5: Contours of solution to (1) with boundary conditions (96) for plastic material response using the finite difference method (solid lines) and the finite element solution (black dots). (a)-(b) displacement and (c)-(f) stress components, with $N_y = N_z = 120$ points.

must be resolved by the grid to ensure accuracy of the solution.

As in *Erickson and Dunham* (2014), we also need to resolve the region of rapid strength degradation immediately behind the tip of a propagating rupture, which is typically much smaller than h^* , and involves the rate- and state parameters a and b in a different manner. By analogy to the

Figure 6: (a) Frictional parameters $a - b$ vary with depth. (b) Normal stress σ_n on fault vs. normal stresses in medium.

corresponding elastic problem (Ampuero and Rubin, 2008), we anticipate that this length scale will be approximately

$$L_b = \frac{\mu^* D_c}{b \sigma_n}. \quad (100)$$

For all of our simulations, events nucleate near the transition zone from velocity weakening to velocity strengthening (at a depth of approximately 10 km) and we chose values for parameters η and h primarily for computational (grid resolution) purposes. Since we use a variable grid spacing, we resolve h^* and L_b in our simulations with at least 60 and 5 grid points (respectively) near the free surface, with fewer (down to 12 and 1 grid point, respectively) at the nucleation depth, which we note seems less than desirable. To test that this grid spacing is adequate, however, we double the number of grid points for one scenario and the results appear qualitatively similar, see Appendix C. For the viscoplastic simulations we resolve the viscous relaxation time scale η/μ with at least 5 time steps.

For some parameter regimes, plastic yielding during the interseismic period is possible. For example, a decrease in cohesion c decreases the size of the elastic domain, so that plastic yielding can occur at lower stress states, see

Figure 7: Snapshots of cumulative slip profiles plotted at 5-s intervals during interseismic period when $\max(V) \leq 1$ mm/s and dashed red profiles plotted at 1 s intervals during quasi-dynamic rupture for (a) elastic reference case, (b) $\eta = 0$ GPa-s, $h = 20$ GPa, $c = 50$ MPa, and (c) $\eta = 36$ GPa-s, $h = 0$ GPa, $c = 50$ MPa.

Figure 2. Although in reality plastic yielding may occur during all phases of the earthquake cycle, we chose to explore scenarios where plastic response is limited to the coseismic phase. This choice was made because viscoplasticity introduces the time scale η/h which must be resolved by the time-stepping method. For small values of η/h , the effective response during rupture is plastic. Unfortunately, small η/h cannot be resolved during the interseismic phase without taking unreasonably small time steps, thus we considered large values of c such that plastic response occurs only at those stress levels attained during rupture. The study of plastic yielding during all phases of the earthquake cycle are deferred to future work.

Figures 7 and 8 show cumulative slip profiles plotted at 5-s intervals during the interseismic period, which we define to be when $\max(V) \leq 1$

Figure 8: Snapshots of cumulative slip profiles plotted at 5-s intervals during interseismic period when $\max(V) \leq 1$ mm/s and dashed red profiles plotted at 1 s intervals during quasi-dynamic rupture for (a) $\eta = 28$ GPa-s, $h = 0$ GPa, $c = 50$ MPa, (b) $\eta = 36$ GPa-s, $h = 20$ GPa, $c = 50$ MPa, and (c) $\eta = 36$ GPa-s, $h = 20$ GPa, $c = 40$ MPa.

mm/s, and in dashed red contours every 1 s during quasi-dynamic rupture. Figure 7(a) is the elastic reference case used in *Erickson and Dunham* (2014), where periodic cycles emerge. Slip below the velocity-weakening region creeps interseismically and approximately 3 m of slip occurs at the surface during each event. Note that during each event, the upper section of the fault catches up with slip at depth, characteristic of an elastic material response. For the plastic simulations, in all cases we found that after the first rupture, slip in the shallow surface is less than the slip at depth. The evolution of this slip deficit with each subsequent event is dictated by the plasticity model, however.

Figure 7(b) shows results from considering rate-independent plasticity with hardening parameter $h = 20$ GPa and cohesion $c = 50$ MPa. Plastic

Figure 9: Off-fault equivalent plastic strain for $\eta = 0$ GPa-s, $h = 20$ GPa, $c = 50$ MPa after the first, second, eighth and eighteenth rupture events. The magnitude and off-fault extent (~ 100 m during first rupture only) of plastic strain effectively saturates after the first event.

response occurs during the first event when the rupture reaches approximately 3 km depth, but has only a slight influence on slip above this depth. During the first rupture, a small slip deficit emerges above ~ 1 km depth. Because hardening causes the yield surface to expand, the response during subsequent events is effectively elastic and the slip deficit remains largely unchanged. Figure 7(c) shows results from a viscoplastic simulation (without hardening) with $\eta = 36$ GPa-s and $c = 50$ MPa. The slip deficit in the upper 3 km increases with subsequent ruptures, and after the tenth event, the slip deficit at the surface is approximately 2 m.

To assess the sensitivity to viscosity, we decrease η from 36 to 28 GPa-s, seen in Figure 8(a). The slip deficit in the upper 3 km also increases with subsequent rupture, and after the 10th event the slip deficit at the surface is approximately 3 m, suggesting that the slip deficit will increase at a faster rate for lower values of η for the viscoplastic model without hardening. Figure 8(b) shows results from combined viscoplastic and hardening effects. For $\eta = 36$ GPa-s, $h = 20$ GPa and $c = 50$ MPa, the slip deficit increases with each rupture, but at a decreasing rate, and reaches a limiting value of ~ 1 m.

Decreasing the cohesion to 40 MPa, as shown in Figure 8(c), generates a larger slip deficit (approximately 3.5 m at the surface after the 10th

Figure 10: Off-fault equivalent plastic strain for $\eta = 36$ GPa-s, $h = 0$ GPa, $c = 50$ MPa after the first, second, eighth and eighteenth rupture events. The magnitude and off-fault extent (additional ~ 100 m per rupture) of plastic strain increases at an approximately constant rate with each rupture during the first 18 events.

event) than the analogous simulation in Figure 8(b), although with hardening present this deficit also saturates after several ruptures.

For the values we considered, cohesion determines the depth at which plastic response occurs during rupture (confined to about 1-2 km below Earth's surface). Figure 9 illustrates the evolution in off-fault equivalent plastic strain for the rate-independent simulation from Figure 7(a), during the first, second, eighth and eighteenth events. The first event generates plastic strain at depths above ~ 1 km and off the fault to about 200 m at the surface. The maximum value at the fault surface is approximately 0.7 millistrain and little increase in either extent or magnitude occurs after the first event. Figure 10 is the analogous figure for the viscoplastic model without hardening from Figure 7(b). The first event generates a maximum value of 0.06 millistrain at the fault surface, extending out to approximately 300 m and to a depth of ~ 1 km. During all subsequent events the maximum value of plastic strain increases.

Adding hardening to the viscoplastic model decreases the magnitude and extent of additional plastic strain with each rupture, see Figure 11, so that by the eighteenth rupture, the distribution remains relatively unchanged by subsequent events. Figure 12 illustrates the effect of a decrease in cohesion

Figure 11: Off-fault equivalent plastic strain for $\eta = 36$ GPa-s, $h = 20$ GPa, $c = 50$ MPa after the first, second, eight and eighteenth rupture events. The magnitude and off-fault extent (~ 100 m during first rupture only) of plastic strain increases at an approximately decreasing rate with each rupture. After 18 events, the extent has saturated at < 1 km at the surface.

(from 50 to 40 MPa) which effectively lowers the yield stress so that plastic straining occurs at lower depths compared to previous simulations. Compared to the results shown in Figure 11, a decrease in cohesion increases the depth of plastic strain from 1 to 2 km during the first event. In addition, a decrease in cohesion generates more plastic strain and with greater extent. By the eighteenth event, plastic strain extends beyond 2 km at the surface.

The amount of tectonic offset accommodated by plastic strain, $u^p(t, z)$, can be computed by integrating the off-fault plastic strain, namely

$$u^p(t, z) = 2 \int_0^{L_y} \gamma_{xy}^p(t, y, z) dy. \quad (101)$$

At the surface $z = 0$, the time history of u^p is plotted in Figure 13 and illustrates how much tectonic offset is accommodated by inelastic deformation for different plasticity models. In particular, when rate-independent plasticity with hardening is used (cyan), the amount of offset due to inelastic deformation is about 0.2 m after the first event and increases almost negligibly after the first event. If a viscoplastic relaxation is added (green), however, the amount of offset is lower during the first event, but increases with each rupture, reaching approximately 0.2 m after ~ 10 events. An increasing amount

Figure 12: Off-fault equivalent plastic strain for $\eta = 36$ GPa-s, $h = 20$ GPa, $c = 40$ MPa after the first, second, eighth and eighteenth rupture events. The magnitude and off-fault extent (~ 1 km during first rupture only) of plastic strain increases at an approximately decreasing rate with each rupture. After 18 events, the extent has begun to saturate near 2 km.

of offset accommodated by inelastic deformation occurs with each rupture for the viscoplastic models without hardening (black, blue, red), with lower values of viscosity generating greater amounts of inelastic deformation. For $\eta = 20$ GPa-s, for example, approximately 2 m of tectonic off-set is accommodated by inelastic strain after ~ 10 events. The rate-independent simulation with hardening present (cyan) reveals that an upper limit to the amount of inelastic deformation exists, by virtue of the fact that hardening causes in expansion of the yield surface, as illustrated in Figure 2. The viscoplastic simulations with hardening (green and purple) show that inelastic yielding continues to occur (with greater overall amounts for lower values in cohesion), but at a decreasing rate, i.e for decreasing du^p/dt . Only the viscoplastic simulations without hardening (black, blue, red) reveal that inelastic yielding continues to occur with an increasing amount of plastic strain accruing with each event ($du^p/dt \geq 0$).

10. Discussion

We have developed a finite difference method to account for off-fault plastic response over many quasi-dynamic ruptures. The computational

Figure 13: Time history of integrated plastic strain at the surface showing amount of tectonic offset accommodated by inelastic deformation.

framework can model both rate-independent plasticity and viscoplasticity, although we found that isotropic hardening is necessary in the rate-independent model for solveability of the underlying equations. We considered a Drucker-Prager model (which reduces to von-Mises plasticity in the antiplane scenario we considered) with a depth-dependent yield stress. Numerical results were verified through convergence tests and comparisons with the solution from a finite element software package. Future work includes a deeper exploration of parameter space. For example, the inclusion of a depth dependency of the internal friction angle and cohesion (like those derived in *Roten et al. (2016)*) will be considered. The effects of hardening and viscosity will further be explored, as our choices for these parameters were chosen primarily for efficiency of computation.

For the parameter study in this work, we found that viscosity, hardening, and cohesion all influence the extent and magnitude of off-fault plastic strain and all scenarios give rise to a shallow slip deficit. The inclusion of hard-

ening in all models sets an upper limit on the slip deficit, which is reached at a faster rate for lower values of viscosity. The viscoplastic models with no hardening, however, give rise to the largest slip deficits which increase continuously with subsequent rupture. Our results suggest that cumulative inelastic deformation over the course of many events can account for a significant amount of tectonic offset. We found that per rupture, ~ 0.1 m of integrated plastic strain accrues, corresponding to $\sim 10\%$ of the tectonic deformation budget. Results from our model compare well to the observations of *Meade et al.* (2013) who estimate that $6\% \pm 9\%$ of deformation occurs off of several major strike-slip faults.

11. Acknowledgments

We thank the editor at JMPS for handling this manuscript, as well as four anonymous reviewers for helpful comments. This work was initiated while B.A.E. was supported by the NSF under Award No. EAR-0948304 and completed with support from NSF under Award No. EAR-1547603 and by the Southern California Earthquake Center. SCEC is funded by NSF Cooperative Agreement EAR-0529922 and USGS Cooperative Agreement 07HQAG0008 (SCEC contribution number 7166).

Appendix A. The Coordinate Transform and Penalty Parameters

As stated in section 6, we desire finer grid resolution in the domain near the fault and close to the free surface $z = 0$. Using coordinate transforms, we map the (y, z) grid in $[0, L_y] \times [0, L_z]$ with unequally spaced nodes, to a computational domain $(\xi_1, \xi_2) \in [0, 1] \times [0, 1]$ with equal grid spacings $(N_{\xi_1} + 1)$ and $N_{\xi_2} + 1$ grid points in each direction, with $\Delta\xi_1 = 1/N_{\xi_1}$, $\Delta\xi_2 = 1/N_{\xi_2}$. We let $N = (N_{\xi_1} + 1)(N_{\xi_2} + 1)$. The mapping is given by

$$y = \ell_Y \tan(\tan^{-1}(L_y/\ell_Y)\xi_1) \quad (\text{A.1a})$$

$$z = \ell_Z \tan(\tan^{-1}(L_z/\ell_Z)\xi_2). \quad (\text{A.1b})$$

Parameters $\ell_Y, \ell_Z > 0$ control the strength to which nodes are clustered near the fault and surface (respectively). The mapping (A.1) is invertible, with $\frac{\partial y}{\partial \xi_1}, \frac{\partial z}{\partial \xi_2} > 0$. The Jacobian J of the transformation is

$$J = \begin{bmatrix} \frac{\partial y}{\partial \xi_1} & 0 \\ 0 & \frac{\partial z}{\partial \xi_2} \end{bmatrix} \quad (\text{A.2})$$

922 with determinant $|\mathbf{J}| = \frac{\partial \mathbf{y}}{\partial \xi_1} \otimes \frac{\partial \mathbf{z}}{\partial \xi_2}$ where $\frac{\partial \mathbf{y}}{\partial \xi_1}$ denotes the diagonal coefficient
 923 matrix, and $\frac{\partial \mathbf{y}}{\partial \xi_1}^{-1}$ is its inverse (reciprocals along the diagonal). Using the
 924 notation introduced in section 6, the SBP-SAT discretization of (33) on the
 925 computational domain is given by

$$\mathbf{0} = \mathbf{D}_{2\xi_1}^{\mathbf{a}_{11}} \mathbf{du} + \mathbf{D}_{\xi_1} \mathbf{a}_{12} \mathbf{D}_{\xi_2} \mathbf{du} + \mathbf{D}_{\xi_2} \mathbf{a}_{21} \mathbf{D}_y \mathbf{du} + \mathbf{D}_{2\xi_2}^{\mathbf{a}_{22}} \mathbf{du} + \tilde{\mathbf{P}}_L + \tilde{\mathbf{P}}_R + \tilde{\mathbf{P}}_T + \tilde{\mathbf{P}}_B, \quad (\text{A.3})$$

926 where the SAT penalty vectors enforcing boundary conditions (41) are

$$\tilde{\mathbf{P}}_L = \mathbf{H}_{\xi_1}^{-1} (\boldsymbol{\alpha}_L + \beta \mathbf{H}_{\xi_2}^{-1} (-\mathbf{a}_{11} \mathbf{S}_{\xi_1} - \mathbf{a}_{12} \mathbf{D}_{\xi_2})^T) \mathbf{H}_{\xi_2} \mathbf{E}_0 (\mathbf{du}_L - \mathbf{dg}_L) \quad (\text{A.4a})$$

$$\tilde{\mathbf{P}}_R = \mathbf{H}_{\xi_1}^{-1} (\boldsymbol{\alpha}_R + \beta \mathbf{H}_{\xi_2}^{-1} (\mathbf{a}_{11} \mathbf{S}_{\xi_1} + \mathbf{a}_{12} \mathbf{D}_{\xi_2})^T) \mathbf{H}_{\xi_2} \mathbf{E}_N (\mathbf{du}_R - \mathbf{dg}_R) \quad (\text{A.4b})$$

$$\tilde{\mathbf{P}}_T = -\mathbf{H}_{\xi_2}^{-1} (\mathbf{I}_{\xi_1} \otimes \mathbf{E}_0) ([-\mathbf{a}_{22} \mathbf{S}_{\xi_2} \mathbf{du} - \mathbf{a}_{21} \mathbf{D}_{\xi_1} \mathbf{du}]_T - \tilde{\mathbf{dg}}_T) \quad (\text{A.4c})$$

$$\tilde{\mathbf{P}}_B = -\mathbf{H}_{\xi_2}^{-1} (\mathbf{I}_{\xi_1} \otimes \mathbf{E}_N) ([\mathbf{a}_{22} \mathbf{S}_{\xi_2} \mathbf{du} + \mathbf{a}_{21} \mathbf{D}_{\xi_1} \mathbf{du}]_B - \tilde{\mathbf{dg}}_B) \quad (\text{A.4d})$$

932 where the modified boundary data are

$$\tilde{\mathbf{dg}}_T = \frac{\partial \mathbf{y}}{\partial \xi_1} \mathbf{dg}_T \quad (\text{A.5a})$$

$$\tilde{\mathbf{dg}}_B = \frac{\partial \mathbf{y}}{\partial \xi_1} \mathbf{dg}_B. \quad (\text{A.5b})$$

935 The modified diagonal coefficient matrices in (A.4) are

$$\mathbf{a}_{11} = \mathbf{C}_{11}^{ep} \left(\frac{\partial \mathbf{y}}{\partial \xi_1}^{-1} \otimes \frac{\partial \mathbf{z}}{\partial \xi_2} \right) \quad (\text{A.6a})$$

$$\mathbf{a}_{12} = \mathbf{C}_{12}^{ep} \quad (\text{A.6b})$$

$$\mathbf{a}_{21} = \mathbf{C}_{21}^{ep} \quad (\text{A.6c})$$

$$\mathbf{a}_{22} = \mathbf{C}_{22}^{ep} \left(\frac{\partial \mathbf{y}}{\partial \xi_1} \otimes \frac{\partial \mathbf{z}}{\partial \xi_2}^{-1} \right) \quad (\text{A.6d})$$

940 correspond to the moduli

$$a_{11} = C_{11}^{ep} \frac{\partial \xi_1}{\partial y} \quad (\text{A.7a})$$

$$a_{12} = C_{12}^{ep} \quad (\text{A.7b})$$

$$a_{21} = C_{21}^{ep} \quad (\text{A.7c})$$

$$a_{22} = C_{22}^{ep} \frac{\partial \xi_2}{\partial z} \quad (\text{A.7d})$$

945 of the transformed (continuous) problem, and we use the notation $a_{11_{i,j}} =$
 946 $a_{11}(y_j, z_i)$ as in section 6. Letting

$$\bar{\mathbf{A}} = \begin{bmatrix} \mathbf{a}_{11} & \mathbf{a}_{12} \\ \mathbf{a}_{21} & \mathbf{a}_{22} \end{bmatrix}, \quad (\text{A.8})$$

symmetry of $\bar{\mathbf{A}}$ follows that of the 2×2 matrix $\bar{\mathbf{C}}^{ep}$ given by (34). That $\bar{\mathbf{A}}$ is positive-definite also follows from $\bar{\mathbf{C}}^{ep}$: Express $\bar{\mathbf{A}}$ via the Schur decomposition $\bar{\mathbf{A}} = \mathbf{X}^T \mathbf{S} \mathbf{X}$, where

$$\mathbf{S} = \begin{bmatrix} \mathbf{a}_{11} & \mathbf{0} \\ \mathbf{0} & \mathbf{a}_{22} - \mathbf{a}_{21} \mathbf{a}_{11}^{-1} \mathbf{a}_{12} \end{bmatrix} \quad (\text{A.9})$$

and

$$\mathbf{X} = \begin{bmatrix} \mathbf{I} & \mathbf{a}_{11}^{-1} \mathbf{a}_{12} \\ \mathbf{0} & \mathbf{I} \end{bmatrix}. \quad (\text{A.10})$$

Since $\mathbf{S}$ is a diagonal matrix, its eigenvalues lie along the diagonal. Positive-definiteness of $\bar{\mathbf{C}}^{ep}$ guarantees that each element along the diagonal of $\mathbf{C}_{11}^{ep}$ is positive and the transformation (A.1) maintains that the diagonal matrix $\mathbf{a}_{11}$ has positive elements. The diagonal matrix $\mathbf{a}_{22} - \mathbf{a}_{21} \mathbf{a}_{11}^{-1} \mathbf{a}_{12} = (\frac{\partial \mathbf{y}}{\partial \xi_1} \otimes \frac{\partial \mathbf{z}}{\partial \xi_2})^{-1} [\mathbf{C}_{11}^{ep}]^{-1} (\mathbf{C}_{11}^{ep} \mathbf{C}_{22}^{ep} - \mathbf{C}_{12}^{ep} \mathbf{C}_{21}^{ep})$ has positive elements by construction of the mapping and positive-definiteness of $\bar{\mathbf{C}}^{ep}$. Thus positive-definiteness of $\bar{\mathbf{A}}$ follows from that of $\mathbf{S}$ by the Sylvester Law of Inertia (*Golub and Van Loan*, 2013).

Applying the energy method to (A.3) and a proper choice of penalty parameters (given shortly) yields $\frac{d}{dt} \mathbf{dE} \leq 0$, where

$$\mathbf{dE} = \frac{1}{2} \mathbf{dU}^T (\mathbf{H}_{\xi_1} \otimes \mathbf{H}_{\xi_2}) \bar{\mathbf{A}} \mathbf{dU} + \frac{1}{2} \mathbf{du}^T (\mathbf{R}_{\xi_1}^{\mathbf{a}_{11}} \otimes \mathbf{H}_{\xi_2}) \mathbf{du} + \frac{1}{2} \mathbf{du}^T (\mathbf{H}_{\xi_1} \otimes \mathbf{R}_{\xi_2}^{\mathbf{a}_{22}}) \mathbf{du} + U_1 + U_2, \quad (\text{A.11})$$

where $\mathbf{dU} = [\mathbf{D}_{\xi_1} \mathbf{du} \ \mathbf{D}_{\xi_2} \mathbf{du}]^T$. U_1 and U_2 are non-negative quantities that arise from the weak enforcement of Dirichlet conditions, detailed shortly.

Note that uniform grid spacing, as considered in section 6, is the special case $\ell_Y, \ell_Z \rightarrow \infty$ and the transformation merely scales the overall size of the domain. In the case of uniform grid spacing, $\bar{\mathbf{A}} = \bar{\mathbf{C}}^{ep}$. The stability results of section 6 are thus a special case of the results here.

The penalty parameters in (A.4) are derived in *Virta and Mattsson* (2014) and given here. The $N \times N$ diagonal coefficient matrix $\mathbf{a}_{11}$ has j, k^{th} entry $\mathbf{a}_{11,j,k}$. *Virta and Mattsson* (2014) find that penalty parameter $\beta = -1$,

and penalty (diagonal) matrices α_L , α_R have components obtained by first defining diagonal matrices $\mathbf{b}_{1L}$, $\mathbf{b}_{1R}$, $\mathbf{b}_{2L}$ and $\mathbf{b}_{2R}$ which have components

$$b_{1L,j,j} = \beta_p(\Delta\xi_1)\lambda_{L,j}/(a_{11,j,1})^2 \quad (\text{A.12a})$$

$$b_{1R,j,j} = \beta_p(\Delta\xi_1)\lambda_{R,j}/(a_{11,j,N_{\xi_1}})^2 \quad (\text{A.12b})$$

$$b_{2L,j,j} = \delta_p(\Delta\xi_1)\lambda_{j,1}/(a_{22,j,1})^2 \quad (\text{A.12c})$$

$$b_{2R,j,j} = \delta_p(\Delta\xi_1)\lambda_{j,N_{\xi_1}}/(a_{22,j,N_{\xi_1}})^2 \quad (\text{A.12d})$$

along the diagonal, where $\beta_p = 36/99$ and $\delta_p = 1/2$ (for the second order operators we consider),

$$\lambda_{L,j} = \min(\lambda_{j,0}, \lambda_{j,1}), j = 0, \dots, N_{\xi_2} \quad (\text{A.13a})$$

$$\lambda_{R,j} = \min(\lambda_{j,N_{\xi_1}-1}, \lambda_{j,N_{\xi_1}}), j = 0, \dots, N_{\xi_2}, \quad (\text{A.13b})$$

and

$$\lambda_{j,k} = \frac{1}{2} \left(a_{11,j,k} + a_{22,j,k} - \sqrt{(a_{11,j,k} - a_{22,j,k})^2 + 4(a_{12,j,k})^2} \right). \quad (\text{A.14a})$$

The positive quantities given in the incremental internal energy are

$$U_1 = \mathbf{U}_L^T \mathbf{H}_3 \mathbf{T}_L \mathbf{U}_L \quad (\text{A.15a})$$

$$U_2 = \mathbf{U}_R^T \mathbf{H}_3 \mathbf{T}_R \mathbf{U}_R \quad (\text{A.15b})$$

for vectors

$$\mathbf{U}_L = [\mathbf{du}_L^T \quad (\mathbf{B}^{\mathbf{a}_{11}} \mathbf{S}_{\xi_1} \mathbf{du})_L^T \quad (\mathbf{a}_{12} \mathbf{D}_{\xi_1} \mathbf{du})_L^T]^T, \quad (\text{A.16a})$$

$$\mathbf{U}_R = [\mathbf{du}_R^T \quad (\mathbf{B}^{\mathbf{a}_{11}} \mathbf{S}_{\xi_1} \mathbf{du})_R^T \quad (\mathbf{a}_{12} \mathbf{D}_{\xi_1} \mathbf{du})_R^T]^T, \quad (\text{A.16b})$$

$$\mathbf{H}_3 = \text{diag}([\mathbf{H}_{\xi_1} \otimes \mathbf{H}_{\xi_2}, \quad \mathbf{H}_{\xi_1} \otimes \mathbf{H}_{\xi_2}, \quad \mathbf{H}_{\xi_1} \otimes \mathbf{H}_{\xi_2}]). \quad (\text{A.16c})$$

Matrix $\mathbf{B}^{\mathbf{a}_{11}}$ is a coefficient matrix for $\mathbf{a}_{11}$ formed in a special way (see *Virta and Mattsson* (2014) for details). Matrices

$$\mathbf{T}_L = \begin{bmatrix} -\alpha_L & -1 & -1 \\ -1 & \mathbf{b}_{1R} & \mathbf{0} \\ -1 & \mathbf{0} & \mathbf{b}_{2R} \end{bmatrix} \quad (\text{A.17a})$$

and

$$\mathbf{T}_R = \begin{bmatrix} -\alpha_R & -1 & -1 \\ -1 & \mathbf{b}_{1L} & \mathbf{0} \\ -1 & \mathbf{0} & \mathbf{b}_{2L} \end{bmatrix} \quad (\text{A.18a})$$

are shown to be positive semi-definite if

$$\alpha_{Lj,j} \leq -\frac{1}{b_{1Rj,j}} - \frac{1}{b_{2Rj,j}}, \quad j = 0, \dots, N_{\xi_2} \quad (\text{A.19a})$$

$$\alpha_{Rj,j} \leq -\frac{1}{b_{1Rj,j}} - \frac{1}{b_{2Rj,j}}, \quad j = 0, \dots, N_{\xi_2} \quad (\text{A.19b})$$

(Virta and Mattsson, 2014).

Appendix B. The Consistent Tangent Moduli

The consistent tangent moduli for both rate-independent and viscoplasticity are derived here simultaneously. Applying a backward-Euler discretization to the flow rule (19), we have

$$\sigma_{ij}^{n+1} = C_{ijkl}(\epsilon_{kl}^{n+1} - \epsilon_{kl}^{p,n+1}) = C_{ijkl}(\epsilon_{kl}^{n+1} - \epsilon_{kl}^{p,n} - d\lambda^{n+1} \frac{s_{kl}^{n+1}}{2\bar{\tau}^{n+1}}). \quad (\text{B.1})$$

The consistent elastoplastic tangent stiffness tensor $\mathcal{C}_{ijkl}^{ep,n+1} = \frac{\partial \sigma_{ij}^{n+1}}{\partial \epsilon_{kl}^{n+1}}$ can be computed by first defining a few terms. Following *Simo and Hughes* (1998), let $n_{ij} = s_{ij}/2\bar{\tau}$. Then

$$\frac{\partial n_{ij}}{\partial s_{kl}} = \frac{1}{\bar{\tau}} \left[\frac{1}{2} I_{ijkl} - n_{ij} n_{kl} \right], \quad (\text{B.2})$$

where the fourth order, symmetric identity tensor

$$I_{ijkl} = \frac{1}{2} [\delta_{ik} \delta_{jl} + \delta_{il} \delta_{jk}]. \quad (\text{B.3})$$

It is a quick exercise to show that

$$n_{ij}^{*,n+1} = n_{ij}^{n+1}, \quad (\text{B.4})$$

and therefore we have

$$\frac{\partial \bar{\tau}^{*,n+1}}{\partial \epsilon_{kl}^{n+1}} = \frac{1}{\bar{\tau}^{*,n+1}} \sigma_{kl}^{*,n+1} \mu = 2\mu n_{kl}^{*,n+1} = 2\mu n_{kl}^{n+1}. \quad (\text{B.5})$$

Next, recall the plastic consistency condition (71), which can be expressed

$$\bar{\tau}^{*,n+1} - \sigma_Y - h\gamma_p^n = (\eta/dt + \mu + h)d\lambda^{n+1} \quad (\text{B.6})$$

where the rate-independent case is obtained by taking $\eta = 0$. Taking the partial derivative of (B.6) yields

$$\frac{\partial \bar{\tau}^{*,n+1}}{\partial \epsilon_{kl}^{n+1}} = (\eta/dt + \mu + h) \frac{\partial d\lambda^{n+1}}{\partial \epsilon_{kl}^{n+1}}. \quad (\text{B.7})$$

Re-arranging (B.7) and substituting in (B.5) yields

$$\frac{\partial \Delta \lambda^{n+1}}{\partial \epsilon_{kl}^{n+1}} = \frac{2\mu}{\eta/dt + \mu + h} n_{kl}^{n+1}. \quad (\text{B.8})$$

Also note that we have,

$$C_{ijmn} \frac{\partial s_{mn}}{\partial \epsilon_{kl}} = 2\mu \frac{\partial s_{ij}}{\partial \epsilon_{kl}}. \quad (\text{B.9})$$

Therefore

$$\frac{\partial n_{ij}^{n+1}}{\partial \epsilon_{kl}^{n+1}} = \frac{\partial n_{ij}^{*,n+1}}{\partial \epsilon_{kl}^{n+1}} = \frac{\partial n_{ij}^{*,n+1}}{\partial \sigma_{mn}^{*,n+1}} \frac{\partial \sigma_{mn}^{*,n+1}}{\partial \epsilon_{kl}^{n+1}} = \frac{\partial n_{ij}^{*,n+1}}{\partial \sigma_{mn}^{*,n+1}} C_{mnkl} = 2\mu \frac{\partial n_{ij}^{*,n+1}}{\partial \sigma_{kl}^{*,n+1}} = 2\mu \frac{\partial n_{ij}^{n+1}}{\partial s_{kl}^{n+1}}. \quad (\text{B.10})$$

When plastic straining is occurring (i.e. when $\lambda > 0$), we can compute the consistent elastoplastic tangent stiffness tensor by taking the partial derivative of equation (B.1)

$$\mathcal{C}_{ijkl}^{ep,n+1} = \frac{\partial \sigma_{ij}^{n+1}}{\partial \epsilon_{kl}^{n+1}} = C_{ijkl} - \frac{\partial d\lambda^{n+1}}{\partial \epsilon_{kl}^{n+1}} \mu n_{ij}^{n+1} - d\lambda^{n+1} \mu \frac{\partial n_{ij}^{n+1}}{\partial \epsilon_{kl}^{n+1}} \quad (\text{B.11})$$

$$= C_{ijkl} - \frac{2\mu}{\eta/dt + \mu + h} n_{kl}^{n+1} 2\mu n_{ij}^{n+1} - d\lambda^{n+1} 2\mu \left(2\mu \frac{\partial n_{ij}^{n+1}}{\partial s_{kl}^{n+1}} \right) \quad (\text{B.12})$$

$$= C_{ijkl} - \frac{4\mu^2}{\eta/dt + \mu + h} n_{kl}^{n+1} n_{ij}^{n+1} - d\lambda^{n+1} 4\mu^2 \frac{1}{\bar{\tau}^{n+1}} \left[\frac{1}{2} I_{ijkl} - n_{ij}^{n+1} n_{kl}^{n+1} \right] \quad (\text{B.13})$$

and the specific case for antiplane motion given in (73)-(75) for rate-independent plasticity, and (78)-(80) for viscoplasticity follow, using the notation $\mathcal{C}_{11}^{ep} = \mathcal{C}_{xyxy}^{ep}$, $\mathcal{C}_{22}^{ep} = \mathcal{C}_{xzxz}^{ep}$, $\mathcal{C}_{12}^{ep} = \mathcal{C}_{xyxz}^{ep}$, $\mathcal{C}_{21}^{ep} = \mathcal{C}_{xzxxy}^{ep}$.

Appendix C. Mesh Refinement

We double the number of grid points used in the simulation shown in Figure 7(c) with $\eta = 36$, $h = 0$ and $c = 50$ MPa, see Fig. C.14. Although a bit more slip occurs with each rupture when mesh refining (note last event for each simulation, for example), the results appear qualitatively similar.

Figure C.14: Snapshots of cumulative slip profiles plotted at 5-s intervals during interseismic period when $\max(V) \leq 1$ mm/s and dashed red profiles plotted at 1 s intervals during quasi-dynamic rupture for $\eta = 36$ GPa-s, $h = 0$ GPa, $c = 50$ MPa for (a) the coarse grid simulation from Fig. 7(c) (plotted again for ease of comparison) and (b) results when using twice the number of grid points.

- 1042 Aagaard, B. T., Knepley, M. G. and Williams, C. A. (2013), A domain
1043 decomposition approach to implementing fault slip in finite-element models
1044 of quasi-static and dynamic crustal deformation, *J. Geophys. Res.*, **118**,
1045 3059–3079, doi:10.1002/jgrb.50217
- 1046 Allison, K. L. and Dunham, E. M. (2016), Earthquake cycle simulations with
1047 rate-and-state friction and nonlinear Maxwell rheology. *Tectonophysics*,
1048 submitted.
- 1049 Ampuero, J.-P. and Rubin, A. M. (2008), Earthquake nucleation on rate
1050 and state faults: Aging and slip laws, *J. Geophys. Res.*, **113**, B01302, doi:
1051 10.1029/2007JB005082.
- 1052 Barbot, S., Lapusta, N. and Avouac, J.-P. (2012), Under the hood of the
1053 earthquake machine: Toward predictive modeling of the seismic cycle, *Sci-*
1054 *ence*, **336**, 707–710, doi:10.1126/science.1218796.
- 1055 Ben-Zion, Y. and Sammis, C. (2011), Brittle Deformation of Solid and Gran-
1056 ular Materials with Applications to Mechanics of Earthquakes and Faults,
1057 *Pure Appl. Geophys.*, **168**, 2147–2149, doi:10.1007/s00024-011-0418-8.

- 1058 Bower, A. F. (2010), Applied Mechanics of Solids, Taylor and Francis Group,
1059 LLC, CRC Press, Boca Raton, FL.
- 1060 Chen, W. F. and Han, D. J. (1988), *Plasticity for Structural Engineers*, first
1061 ed., Springer-Verlag, New York, 1–606.
- 1062 Chester, F. M., Evans, J. P. and Biegel, R. L. (1993), Internal structure
1063 and weakening mechanisms of the San Andreas fault, *J. Geophys. Res.*, **98**,
1064 771–786, doi:10.1029/92JB01866.
- 1065 Chester, F. M. and Logan, J. M. (1986), Implications for mechanical prop-
1066 erties of brittle faults from observations of the Punchbowl fault zone, Cal-
1067 ifornia, *Pure Appl. Geophys.*, **124**, 79–106 doi:10.1007/BF00875720.
- 1068 de Souza Neto, E. A., Perić, D. and Owen, D. R. J. (2008), *Computational*
1069 *Methods for Plasticity*, first ed., John Wiley & Sons Ltd, United Kingdom,
1070 1–791. DeSouza
- 1071 Dieterich, J. H. (1979), Modeling of rock friction: 1. Experimental results
1072 and constitutive equations, *J. Geophys. Res.*, **84**, 2161–2168, doi:10.1029/
1073 JB084iB05p02161.
- 1074 Drucker, D. C. (1959), A definition of a stable inelastic material, *J. Appl.*
1075 *Mech. ASME*, **26**, 101–195.
- 1076 Dunham, E. M., Belanger, D., Cong, L. and Kozdon, J. E. (2011a), Earth-
1077 quake ruptures with strongly rate-weakening friction and off-fault plastic-
1078 ity, Part 1: Planar faults, *Bull. Seismol. Soc. Am.*, **101**, 5, 2296–2307,
1079 doi:10.1785/0120100075.
- 1080 Dunham, E. M., Belanger, D., Cong, L. and Kozdon, J. E. (2011b), Earth-
1081 quake ruptures with strongly rate-weakening friction and off-fault plastic-
1082 ity, Part 2: Nonplanar faults, *Bull. Seismol. Soc. Am.*, **101**, 5, 2308–2322,
1083 doi:10.1785/0120100076.
- 1084 Dunne, F. and Petrinic, N. (2006), *Introduction to Computational Plasticity*,
1085 first ed., Oxford University Press, New York, 1–242.
- 1086 Duru, K. and Virta, K. (2014), Stable and high order accurate difference
1087 methods for the elastic wave equation in discontinuous media, *J. Comp.*
1088 *Phys.*, **279**, 37–62, doi:10.1016/j.jcp.2014.08.046.

- 1089 Erickson, B. A., and Dunham, E. M. (2014), An efficient numerical method
1090 for earthquake cycles in heterogeneous media: Alternating subbasin and
1091 surface-rupturing events on faults crossing a sedimentary basin, *J. Geophys.*
1092 *Res.*, **119**, 1–27, doi:10.1002/2013JB010614.
- 1093 Faulkner, D. R., Jackson, C. A. L., Lunn, R. J., Schlische, R. W., Shipton, Z.
1094 K., Wibberley, C. A. J. and Withjack, M. O. (2010), A review of recent
1095 developments concerning the structure, mechanics and fluid flow properties
1096 of fault zones, *J. Struct. Geol.*, **32**, 11, 1557–1575, doi:10.1016/j.jsg.2010.
1097 06.009.
- 1098 Gabriel, A.-A., Ampuero, J.-P., Dalguer, L. A. and Mai, P. M. (2013), Source
1099 properties of dynamic rupture pulses with off-fault plasticity, *J. Geophys.*
1100 *Res.*, **118**, 8, 4117–4126, doi:10.1002/jgrb.50213.
- 1101 Gabriel, A.-A., Ampuero, J.-P., Dalguer, L. A. and Mai, P. M. (2013),
1102 The transition of dynamic rupture styles in elastic media under
1103 velocity-weakening friction, *J. Geophys. Res.*, **117**, B09311, doi:10.1029/
1104 2012JB009468.
- 1105 Glowinski, R., and Le Tallec, P. (1989), Augmented Lagrangian and Opera-
1106 tor Splitting Methods in Nonlinear Mechanics, Society for Industrial and
1107 Applied Mathematics, Philadelphia, Volume 9.
- 1108 Golub, G. H. and Van Loan, C. F. (2013), Matrix Computations, 4th edition,
1109 JHU press, Baltimore.
- 1110 Gustafsson, B. (2008), High Order Difference Methods for Time Dependent
1111 PDE, Springer-Verlag, Berlin, doi:10.1007/978-3-540-74993-6.
- 1112 Horn, R. A. and Johnson, C. R. (1985), Matrix Analysis, Cambridge Univer-
1113 sity Press, New York.
- 1114 Jain, S. K. (2008), Introduction to Theories of Plasticity, Part 1: Stress-
1115 Strain Relations, Engineering Publications, Virginia.
- 1116 Johnson, K. M. and Segall, P. (2004), Viscoelastic earthquake cycle mod-
1117 els with deep stress-driven creep along the San Andreas fault system, *J.*
1118 *Geophys. Res.*, **109**, B10403, doi:10.1029/2004JB003096.

- 1119 Kaneko, Y., Ampuero, J.-P. and Lapusta, N. (2011), Spectral-element simu-
 1120 lations of long-term fault slip: Effect of low-rigidity layers on earthquake-
 1121 cycle dynamics, *J. Geophys. Res.*, **116**, B10313, 1–18, doi:10.1029/
 1122 2011JB008395.
- 1123 Kaneko, Y., and Fialko, Y. (2011), Shallow slip deficit due to large strike-slip
 1124 earthquakes in dynamic rupture simulations with elasto-plastic off-fault
 1125 response, *Geophys. J. Int.*, **186**, 1389–1403, doi:10.1111/j.1365-246X.2011.
 1126 05117.x.
- 1127 Kozdon, J. E., Dunham, E. M. and Nordström, J. (2012), Interaction of waves
 1128 with frictional interfaces using summation-by-parts difference operators:
 1129 Weak enforcement of nonlinear boundary conditions, *J. Sci. Comput.*, **50**,
 1130 341–367, doi:10.1007/s10915-011-9485-3.
- 1131 Kreiss, H.-O. and Scherer, G. (1974), Finite element and finite difference
 1132 methods for hyperbolic partial differential equations, Mathematical aspects
 1133 of finite elements in partial differential equations, Academic Press, Inc.,
 1134 195–212, doi:10.1016/B978-0-12-208350-1.50012-1.
- 1135 Kreiss, H.-O. and Scherer, G. (1977), On the existence of energy estimates for
 1136 difference approximations for hyperbolic systems, *Technical Report*, Dept.
 1137 of Scientific Computing, Uppsala University.
- 1138 Lapusta, N., Rice, J. R., Ben-Zion, Y. and Zheng, G. (2000), Elastodynamic
 1139 analysis for slow tectonic loading with spontaneous rupture episodes on
 1140 faults with rate-and-state dependent friction, *J. Geophys. Res.*, **105**, 23765–
 1141 23789, doi:10.1029/2000JB900250.
- 1142 Ma, S. and Andrews, D. J. (2010), Inelastic off-fault response and three-
 1143 dimensional earthquake rupture dynamics on a strike-slip fault, *J. Geo-
 1144 phys. Res.*, **115**, B04304, doi:10.1029/2009JB006382.
- 1145 Marone, C. (1998), Laboratory-derived friction laws and their application to
 1146 seismic faulting, *Annu. Rev. Earth Planet. Sci.*, **26**, 643–696, doi:10.1146/
 1147 annurev.earth.26.1.643.
- 1148 Mattsson, K. (2011), Summation by parts operators for finite difference ap-
 1149 proximations of second-derivatives with variable coefficients, *J. Sci. Com-
 1150 put.*, **51**, 650–682, doi:10.1007/s10915-011-9525-z.

- 1151 Mattsson, K. and Nordström, J. (2004), Summation by parts operators for
 1152 finite difference approximations of second derivatives, *J. Comput. Phys.*,
 1153 **199**, 503–540, doi:10.1016/j.jcp.2004.03.001.
- 1154 Mattsson, K., Ham, F. and Iaccarino, G. (2008), Stable and accurate wave-
 1155 propagation in discontinuous media, *J. Comput. Phys.*, **227**, 8753–8767
 1156 doi:10.1016/j.jcp.2004.03.001.
- 1157 Mazzoni, S., McKenna, F., Scott, M. H., and Fenves, G. L., (2009), Open
 1158 system for earthquake engineering simulation user manual. University of
 1159 California, Berkeley.
- 1160 Meade, B. J., Klinger, Y., and Hetland, E. A., (2013), Inference of multiple
 1161 earthquake-cycle relaxation timescales from irregular geodetic sampling of
 1162 interseismic deformation, *Bull. Seismol. Soc. Am.*, **103**, 2824–2835 doi:
 1163 10.1785/0120130006.
- 1164 Mitchell, T. M. and Faulkner, D. R. (2009), The nature and origin of off-fault
 1165 damage surrounding strike-slip fault zones with a wide range of displace-
 1166 ments: A field study from the Atacama fault zone, northern Chile, *J.*
 1167 *Struct. Geol.*, **31**, 8, 802–816, doi:10.1016/j.jsg.2009.05.002.
- 1168 Nordström, J., Mattsson, K. and Swanson, C. (2007), Boundary conditions
 1169 for a divergence free velocity-pressure formulation of the Navier-Stokes
 1170 equations, *J. Comput. Phys.*, **225**, 874–890, doi:10.1016/j.jcp.2007.01.010.
- 1171 Perzyna, P. (1966), Fundamental Problems in Viscoplasticity, *Advances*
 1172 *in Applied Mechanics*, **9**, 243 - 377, doi:http://dx.doi.org/10.1016/
 1173 S0065-2156(08)70009-7.
- 1174 Perzyna, P. (1971), Thermodynamic Theory of Viscoplasticity, *Advances*
 1175 *in Applied Mechanics*, **11**, 313 - 354, doi:http://dx.doi.org/10.1016/
 1176 S0065-2156(08)70345-4.
- 1177 Power, W. L and Tullis, T. E. (1991), Euclidean and fractal models for the
 1178 description of rock surface roughness, *J. Geophys. Res.*, **96**, B1, 415–424,
 1179 doi:10.1029/90JB02107.
- 1180 Ranjith, K. (2008), Dynamic anti-plane sliding of dissimilar anisotropic
 1181 linear elastic solids, *Int. J. Solids Struct.*, **45**, 4211–4221, doi:10.1016/j.
 1182 ijsolstr.2008.03.002.

- 1183 Rice, J. R. (1992), Fault stress states, pore pressure distributions and the
1184 weakness of the San Andreas fault, in *Fault Mechanics and Transport Prop-*
1185 *erties of Rock*, edited by Evans, B. and Wong, T.-F., 475 – 503, Academic,
1186 San Diego, Calif.
- 1187 Rice, J. R. (1993), Spatio-temporal complexity of slip on a fault, *J. Geophy.*
1188 *Res.*, **98**, 9985–9907, doi:10.1029/93JB00191.
- 1189 Roache, P. (1998), *Verification and Validation in Computational Science and*
1190 *Engineering*, first ed., Hermosa Publishers, Albuquerque.
- 1191 Roten, D., Olsen, K. B., Day, S. M. and Cui, Y. (2016), Quantification of
1192 fault zone plasticity effects with spontaneous rupture simulations, *Work-*
1193 *shop on Best Practices in Physics-Based Fault Rupture Models for Seismic*
1194 *Hazard Assessment of Nuclear Installations*, 18–20 November 2015, Vi-
1195 enna, Unpublished conference paper.
- 1196 Ruina, A. (1983), Slip instability and state variable friction laws, *J. Geophy.*
1197 *Res.*, **88**, B12, 10359–10370, doi:10.1029/JB088iB12p10359.
- 1198 Scalerandi M., Delsanto, P. P., Chiroiu, C. and Chiroiu, V. (1999), Numerical
1199 simulation of pulse propagation in nonlinear 1-D media, *J. Acoust. Soc.*
1200 *Am.*, **106**, doi:10.1121/1.428078.
- 1201 Shi, Z. and Day, S. M. (2013), Rupture dynamics and ground motion from 3-
1202 D rough-fault simulations, *J. Geophy. Res.*, **118**, 1122–1141, doi:10.1002/
1203 jgrb.50094.
- 1204 Shipton, Z. K., Evans, J. P. and Thompson, L. B. (2005), The geometry
1205 and thickness of deformation-band fault core and its influence on sealing
1206 characteristics of deformation-band fault zones, in *Faults, Fluid Flow, and*
1207 *Petroleum Traps*, AAPG Mem., **85**, edited by R. Sorkabi and Y. Tsuji,
1208 181–195, American Association of Petroleum Geologists, Tulsa, Okla.
- 1209 Simo, J. C. and Taylor, R. L. (1985), Consistent tangent operators for rate-
1210 independent elastoplasticity, *Comput. Methods Appl. Mech. Eng.*, **48**, 101–
1211 118, doi:10.1016/0045-7825(85)90070-2.
- 1212 Simo, J. C. and Hughes, T. J. R. (1998), *Computational Inelasticity*, first
1213 ed., Springer, New York, doi:10.1007/b98904.

- 1214 Svärd, M. and Nordström, J. (2014), Review of summation-by-parts schemes
1215 for initial-boundary-value problems, *J. Comput. Phys.*, **268**, 17–38, doi:
1216 10.1016/j.jcp.2014.02.031.
- 1217 Templeton, E. and Rice, J. R. (2008), Off-fault plasticity and earthquake
1218 rupture dynamics: 1. Dry materials or neglect of fluid pressure changes, *J.*
1219 *Geophys. Res.*, **113**, B09306, doi:10.1029/2007JB005529.
- 1220 Thompson, T. B. and Meade, B. J. (2016), Next generation boundary element
1221 models for earthquake science, Poster Presentation at 2016 SCEC Annual
1222 Meeting.
- 1223 Tullis, T. E., Richards-Dinger, K., Barall, M., Dietrich, J. H., Field, E. H.,
1224 Heien, E. M., Kellog, L. H., Pollitz, F. F., Rundle, J. B., Sachs, M. K., Tur-
1225 cotte, D. L., Ward, S. N. and Yikilmaz, M. B. (2012), Generic earthquake
1226 simulator, *Seismol. Res. Lett.*, **83**, 959–963, doi:10.1785/0220120093.
- 1227 Virta, K. and Mattsson, K. (2014), Acoustic wave propagation in complicated
1228 geometries and heterogeneous media, *J. Sci. Comput.*, **61**, doi:10.1007/
1229 s10915-014-9817-1.
- 1230 Xu, S., Ben-Zion, Y. and Ampuero, J.-P. (2012), Properties of inelas-
1231 tic yielding zones generated by in-plane dynamic ruptures: I. Model
1232 description and basic results, *Geophys. J. Int.*, **191**, 1325–1342, doi:
1233 10.1111/j.1365-246X.2012.05679.x.
- 1234 Xu, S., Ben-Zion, Y. and Ampuero, J.-P. (2012), Properties of inelastic yield-
1235 ing zones generated by in-plane dynamic ruptures: II. Detailed parameter-
1236 space study, *Geophys. J. Int.*, **191**, 1343–1360, doi:10.1111/j.1365-246X.
1237 2012.05685.x.